

INDEX

A

Absorber. *See* Cooling, absorption

Absorptance, absorptivity, absorption (of light) 1286–1287

Absorption cooling. *See* Cooling, absorption

Accumulator, refrigerant 1301. *See* Receiver, refrigerant

Acid dew point

of fuels 1249

Acid dew point, flue gas

definition 122–123

in boiler air preheaters 128

in boiler economizers. *See* Economizers, boiler

Acid dew point, of fuels 123

Active solar systems. *See* Solar cooling; Solar heating, active

Adjustable-pulley drives. *See* Drives, variable-pulley

Adjustable-speed drives. *See* Drives, variable-speed

Adsorbent air filters 541

Affinity laws (pumps) 1340

Air cleaning. *See* Filters, air

to reduce ventilation

requirements. *See* Ventilation,

outside air: reduce, by air cleaning

Air conditioners

compressor heaters, turn off **770**

compressors, install efficient **767**

condensing temperature, optimize **768–769**

efficiency ratings. *See* Efficiency ratings, cooling

electric heat, eliminate **761**

electric heating elements, eliminate **771**

fan motors, install efficient **756**

heat recovery from **773–774**

heat rejection equipment

control to minimize operation **772**

drain seasonally **770–771**

heat sinks, install alternative **775–778**

design issues 777

options in new construction 775–776

options in retrofit 776–777

where to consider 775

infiltration around, prevent **757**

install efficient **759–760, 767**

cost, relative 760

efficiency ratings 759

other features 760

size, relative 760

maintenance

for self-contained units **754–756**

for split systems **765–766**

motors, install efficient **766**

ventilation, eliminate inefficient **758**

Air conditioning. *See* Cooling

Air ejectors

in vacuum condensate systems 140

Air handling systems

& building pressure. *See* Pressure, building

air cleaning, to reduce

ventilation. *See* Ventilation,

outside air: air cleaning, to reduce amount

dampers, control. *See* Dampers, control

dampers, infiltration. *See* Dampers, infiltration

dual-duct reheat. *See* Air handling systems, dual-duct reheat

dual-duct VAV. *See* Air handling systems, VAV dual-duct

economizer cycle. *See* Economizer, outside air

energy waste by, causes 499–500

envelope penetrations, improve **563–567**

exhaust recirculation 566

exploit ambient temperature 566–567

freeze protection 571–572

pollutant sources 563–565

problems related to 563

wind, shielding from 565

fans, relief air 533

arrangement 524

capacity of 533–534

from spaces 537

fans, return air 532–533

arrangement 524

capacity of 533–534

control of space pressure 532–

533

fans, supply air

control of output. *See* Air

handling systems, by type

pressure requirements of filters 545

filters. *See* Filters, air

freeze protection, minimize energy for **568–572**

& building penetrations. *See* Air

handling systems: envelope

penetrations, improve

by antifreeze in coils 568

by draining coils 568

by preheat coils 569–570

coil valve leakage 572

during system shutdown 571–572

of steam coils 568–569

stratification, avoid. *See* Air handling systems: stratification,

avoid

front end

& economizer cycle 536, 548

& stratification 575–576

configurations 522–524, 532–537

dampers, control 532–533

definition 498

improvement of **532–537**

functions 497–498

heat recovery. *See* Heat recovery,

from building exhaust air

induction. *See* Air handling systems, induction

maintenance

access for 536

minimizing operation. *See* Air handling systems, minimize operation

multizone. *See* Air handling

systems, multizone

once-through. *See also* Air handling systems, by type

provide recirculation for **538–539**

purge cycle. *See* Purge cycle, air handling system

return air path

corridor 538

ducted 538

plenum 538

through void 538

- single-duct reheat. *See* Air handling systems, single-duct reheat
- single-duct VAV. *See* Air handling systems, VAV single-duct
- single-zone. *See* Air handling systems, single-zone
- stratification, avoid 536, **573–578**
 - by damper arrangement 576
 - by damper turbulence 576
 - by duct configuration 575–576
 - by fan mixing 574–575
 - by mixing vanes 576–577
 - by preheat coils 575
 - how to minimize 574–578
 - how to visualize 574
 - problems caused by 573
 - thermostat installation 574
- triple-duct. *See* Air handling systems, triple-duct
- types of air handling systems 498
- VAV dual-duct. *See* Air handling systems, VAV dual-duct
- VAV single-duct. *See* Air handling systems, VAV single-duct
- ventilation by. *See* Ventilation, outside air
- Air handling systems, dual-duct reheat**
 - coils, turn off to avoid reheat **643** & duct temperature reset 643
 - energy saving 643
 - when to do 643
 - comfort characteristics 637
 - convert to multi-speed fan **644**
 - convert to VAV **644–650**. *See also* Air handling systems, VAV dual-duct
 - air circulation in space 648
 - building pressure control 650
 - conversion steps 646–650
 - diffuser performance 648
 - duct layout 649–650
 - duct temperature reset 649
 - economizer cycle 650
 - energy saving 645–646
 - fan modulation control 649
 - fan modulation methods 649
 - fan-induced resonances 650
 - isolation of unoccupied spaces 650
 - minimum-flow settings 648
 - purge cycle 650
 - space temperature deadband 648–649
 - space temperature setback 648
- space warm-up 648
- terminal conversion kits 647
- terminals, reduce resistance 647–648
- ventilation, outside air 649
- description 637
- duct temperatures, optimize **640–641**
 - by automatic reset **642**
 - cooling coils without valves 641
 - energy saving 640
 - how to adjust 640–641
 - humidity, effect on 640
 - load diversity limitations 640
 - placards 641
- economizer cycle limitations 548–550
- energy consumption 638–639
- fan output, trim **644**
- humidity control 637
- reheat
- Air handling systems, induction**
 - avoid discharge on surfaces **699**
 - description 691–692
 - maintenance **698–699**
 - primary air temperature, maximize **693–694**
 - by automatic reset **694**
 - energy saving 693
 - terminal condensate drainage 693
 - space temperature setback, install **696–698**
 - energy saving 696
 - how to install 696–697
 - overrides 697
 - placards 697
 - where to apply 696
 - turn off air handling unit coil **695** & primary air reset 695
 - energy saving 695
- Air handling systems, minimize operation**
 - automatic control, prefer 506
 - by administrative staff **515**
 - by annunciator panel **516**
 - by clock control **507–508**
 - how to select controls 507
 - override by occupants 508
 - where to consider 507
 - by optimum-start control **509–510** & control of other equipment 510
 - equipment options 509
 - how it works 509
 - outside air sensor, how to install 509
 - vs. setback temperature control 510
- by personnel sensor **513–514**
 - limitations 513
 - placards for 514
 - tailoring to space 513–514
 - types of sensors 513
- by rundown timer **511–512**
 - advantages 511
 - limitations 511–512
 - placards for 512
 - types of time switches 512
 - where to install 511
- energy saving 506
- override by occupants 506
- temperature limits 506
- vs. temperature setback 507
- Air handling systems, multizone**
 - coils, turn off seasonally **654**
 - comfort characteristics 651–652
 - convert to multi-speed motor **655**
 - convert to VAV **656–659**
 - air flow, minimum settings 658
 - conversion steps 656–659
 - dampers, control of 657
 - dampers, how to modify 657
 - deck temperature reset 658
 - diffuser performance 658
 - economizer cycle 658
 - energy saving 656
 - fan modulation, control of 657–658
 - fan modulation methods 657
 - fan-induced resonances 658
 - humidity control 658
 - isolation of individual zones 658
 - purge cycle 658
 - retrofit difficulty 656
 - space air velocity 658
 - ventilation, outside air 658
 - zone layout 658
 - zone pressure variations 658
 - zone temperature deadband 658
 - zone temperature setback 658
 - damperless 653
 - deck temperatures, optimize **654**
 - by automatic reset **654**
 - description 651–653
 - economizer cycle limitations 548–550
 - fan output, trim **655**
 - humidity control 651–652
 - reheat energy waste 651
 - three-deck 652–653

Air handling systems, single-duct reheat

air blending terminals, block reheat passage **614–615**
 energy saving 614–615
 how to accomplish 615
 limitations 614
 where to consider 614
 chilled air temperature, set to minimize reheat **607–609**
 by automatic reset **610–611**
 energy saving 607–608
 how to maximize 608
 humidity, effect on 608
 load diversity, limitation by 608
 comfort advantages 606
 convert to heating/cooling terminals **631–633**
 advantages 631
 coils, how to install 632
 control of space pressure 631
 controls 633
 cost 631
 dehumidification at low load 633
 disadvantages 631
 energy saving 631
 fan modulation 633
 installation difficulty 631
 isolation of unoccupied spaces 632
 noise 631
 outside air ventilation 631
 piping 632
 space air circulation 631
 space requirement 631
 vs. VAV 631
 where to consider 631–632
 zoning 632
 convert to multi-speed motor **616–617**
 energy saving 616
 motor, how to select 616
 problems at low air flow 617
 resonances, how to avoid 617
 speed, how to control 616–617
 vs. fan-coil units 631
 vs. VAV 616
 convert to room heating/cooling units **634–635**
 advantages 634
 disadvantages 634
 energy saving 634
 vs. VAV 634

convert to VAV **618–630**. *See also* Air handling systems, VAV single-duct
 chilled air temperature reset 628
 control & adjustments 627–629
 conversion steps 621
 design challenges 619–621
 diffuser performance 620, 626–627
 duct layout 629
 duct pressure reset 628–629
 economizer cycle 629
 energy saving 618–619
 fan modulation methods 627
 fan noise 621
 fan-induced resonances 621
 heating, how to provide 621–622
 heating problems 619
 humidity control 620, 629
 isolation of individual spaces 629–630
 minimum-flow settings 627
 problems at low air flow 619
 purge cycle 629
 space air circulation 620–621
 space pressure control 629
 space pressure variations 621
 space temperature deadband 629
 space temperature setback 629
 space warm-up 629
 terminal unit noise 621, 624
 terminals, fan-powered 621, 624–626
 terminals, how to select 622–623
 ventilation, outside air 619–620, 629
 zoning 629
 description 605
 economizer cycle control 549
 fan output, trim **615**
 fan output, VAV. *See also* Air handling systems, VAV single-duct
 humidity, control of 606
 reheat energy waste 605–606
 turn off cooling coil to avoid reheat **612**
 energy saving 612
 limitations 612
 turn off reheat coils to avoid reheat **613**
 control changes required 613
 energy saving 613
 limitations 613

Air handling systems, single-zone

controls, placards for energy saving 581
 how to design 581–582
 where to install 582
 controls, temperature deadband by adjusting valve actuators **603–604**
 by deadband thermostat **600–602**
 by manual heat/cool switching **597–599**
 by signal offset relay **603–604**
 deadband range 596
 dehumidification, providing 596–597
 energy saving 596
 methods 596
 thermostats, deadband 600–601
 thermostats, heat/cool switching 597–598
 thermostats, hesitation 601
 controls, temperature setback **583–584**
 avoid forcing setback 584
 energy saving 583
 how to accomplish 583–584
 override 584
 placards 584
 description 579
 economizer cycle control 549
 fan output, cycling **588–590** & deadband 590
 energy saving 588–589
 limitations 589–590
 short cycling, avoiding 590
 soft starting 590
 where to consider 588
 fan output, match to load **585–587**
 energy saving 585
 factors to consider 585–587
 methods 585
 fan output, multi-speed motor **591–592**
 electric heating coils, with 592
 energy saving 591
 fan speed ratio 591
 how to control 591–592
 motor selection 591
 placards 592
 resonances, avoiding 592
 fan output, trim **588**
 fan output, VAV **593–595**
 air distribution in space 594
 building pressure control 594
 controls 594

- drive selection 594
- energy saving 593–594
- installation issues 594–595
- outside air control 594
- resonances 594
- where to consider 593
- with DX coils 594
- with electric heating coils 594
- Air handling systems, triple-duct** 639, 682
- Air handling systems, VAV dual-duct**
 - air circulation in space 648
 - building pressure control 650
 - damper overlap, minimize **685**
 - energy saving 685
 - how to adjust 686
 - description 681
 - design steps 646–650
 - diffuser performance 648
 - duct layout 649–650
 - duct temperature reset 649
 - economizer cycle 650
 - economizer cycle, install **689–690**
 - design steps 690
 - energy saving 689
 - ventilation, outside air 689–690
 - vs. waterside economizer 690
 - where to apply 689
 - energy saving 645–646
 - fan modulation control 649
 - fan modulation methods 649
 - fan modulation, optimize **688**
 - fan-induced resonances 650
 - humidity control 649
 - isolation of unoccupied spaces 650
 - maximize deadband **683–684**
 - minimum-flow settings 648
 - optimize duct temperatures **687**
 - by automatic reset **688**
 - placards, thermostat **683**
 - purge cycle 650
 - space temperature deadband 648–649
 - space temperature setback 648
 - space warm-up 648
 - temperature setback, install **684**
 - terminals, how to select 647
 - turn off coils when practical **684**
 - ventilation, outside air 649
 - zoning 649
- Air handling systems, VAV single-duct 618–630**
 - changeover control. *See* Air handling systems, VAV single-duct: terminals, heating/cooling changeover, install
- chilled air temperature reset 620, 628, **672**
 - by automatic control **673**
 - comfort benefit 672
 - energy saving 672
 - ventilation benefit 672
- dehumidification & reheat 620
 - control by humidistat 620, 629
 - problem at low air flow 620
- description 661
- design challenges 619–621
- design steps 621
- diffusers
 - & chilled air temperature reset 620
 - & fan-powered terminal units 620
 - problems at low air flow 620, 626–627
- duct layout 629
- duct pressure reset 628–629
- economizer cycle 629
- energy saving 618–619
 - excess cooling 618–619
 - fan energy 619, 626
 - in once-through systems 619
 - reheat 618–619
- energy waste from reheat 622, 625, 626
- fan modulation, improve **677–680**
 - benefits 677
 - control 628
 - energy saving 677–679
 - methods, comparison 627, 679–680
 - methods, preferred 680
 - resonances 621
- heating
 - space warm-up 621–622
 - with convectors 622
 - with separate equipment 622–623
- heating, how to provide 621–622
- heating problems 619
- isolation of individual spaces 629
- load diversity limitation 676
- noise
 - fan noise 621
 - resonances 621
 - terminal unit noise 621, 624, 626
- placards for space thermostats **662–663**, 665
 - energy saving 662
 - thermostat accessibility 663
 - what to say 662
 - where to use 662
- problems at low air flow 619, 620–621, 626
- purge cycle control 629
- space air circulation 620–621
- space pressure
 - control 629
 - variations 621
- space temperature
 - deadband 629
 - setback 629
- space temperature control
 - morning warm-up 629
- terminals, conventional 622
 - duct pressure, sensitivity to 624
 - externally powered 623
 - heating/cooling changeover 627–628
 - minimum-flow settings 624, 627
 - minimum-flow type 623
 - noise 624
 - pressure-dependent 624
 - pressure-independent 624
 - reheat coils 623
 - reheat energy waste 622, 623
 - retrofit difficulty 624
 - self-powered 623
 - shutoff air leakage 624
 - shutoff type 623
 - shutoff vs. minimum-flow 623
 - system powered 623
- terminals, fan-powered 624–626
 - advantages 625–626
 - control 626
 - cost 626
 - diffuser performance 620
 - disadvantages 626
 - energy waste from reheat 622, 625, 626
 - fan energy 626
 - heat recovery from lighting 625–626, 626
 - noise 626
 - parallel vs. series 626–627
 - parallel-flow 625
 - series-flow 625
 - size 626
 - space air circulation 621, 626
 - types of terminals 625
 - ventilation limitations 625, 626
- terminals, heating/cooling changeover, install **674**
 - control
 - description 674
 - energy saving 674
 - fan modulation, effects 676
 - minimum-flow settings 674–675

- thermostat deadband 676
- thermostat operation 676
- with electric heating coils 675–676
- terminals, how to select 622–624
- terminals, reduce minimum flow **670–671**
 - energy saving 670
 - how to adjust 671
 - limitations 670–671
- thermostats, install deadband **664–666**
 - deadband range 664
 - energy saving 664–665
 - humidity, effect on 664
 - placards 665
 - thermostat placards 668
 - types of deadband thermostats 665, 667–668
 - ventilation, effect on 664
 - where to apply 664
- thermostats, install setback **667–668**
 - energy saving 667
 - limitations 667
 - methods 667
 - overrides 668
- turn off cooling coils **669**
- ventilation, outside air
 - & front end design 620
 - & reheat 619–620
 - control 629
 - uneven distribution to spaces 620
 - with shutoff terminals 620
 - zoning for efficiency 629
- Air leakage, building envelope 1383–1385**
 - & freeze protection 571–572
 - & vapor barriers 1385
 - at curtain wall joints 864
 - at door frames 864
 - at doors. *See* Doors, by type; Weatherstripping
 - at elevator shafts **872**
 - at expansion joints 865–866
 - at foundation plates 865
 - at gaps in structure **864–867**
 - at parapets 866
 - at pipe & wiring penetrations 866
 - at roof hatches. *See* Roof hatches, install efficient
 - at roof-to-wall joints 865
 - at soffits 865
 - at space air vents **870–871**
 - at switches & receptacles **868**
 - at window frames 864
 - at windows **859**
 - avoiding, all methods. *See* Section 6
 - causes of air leakage 1383–1384
 - chimney effect 1383–1385
 - fan operation 1383
 - wind 1383
 - exfiltration 806, 1383
 - how to estimate 1384–1385
 - how to find 866–867, 1384
 - how to seal 867
 - weatherstripping. *See* Weatherstripping
 - where leaks occur 864–866, 870
- Air pollution**
 - & air-fuel ratio 60–61
 - flue sensors 48–49, 54
- Air preheaters, boiler 126–128.** *See also* Economizers, boiler
 - acid condensation in 128
 - cleaning requirements 128
 - draft requirements 128
 - energy savings 126–127
 - types of preheaters 127–128
 - heat pipe 127–128
 - parallel-plate 127
 - rotary 127
 - tubular 127
 - where to install 126–127
- Air-cooled condensers.** *See also* Heat rejection equipment
 - definition 1302
- Air-cooled condensing units**
 - definition 1302
- Air-fuel ratio 59**
 - & boiler maintenance **69–70**, 111
 - & burner maintenance 73
 - & burner type 79
 - & flue draft 64
 - adjusting **60–64**
 - atmospheric gas burners 62–63
 - basic procedures 61, 62–64
 - excess air 62
 - how often 64
 - linkages 69–70
 - modulating burners 63–64
 - automatic controls **65–69**
 - actuators 66, 68, 69–70, 70
 - adaptability to load 68
 - adaptability to multiple fuels 68
 - alarms 66, 68
 - calibration 67–68, 70
 - components of 66
 - control response 68
 - data logging 68
 - displays 66, 68
 - energy savings 65
 - fail-safe features 68
 - how to select 66–69
 - installation 66
 - overrides 68
 - reliability 66
 - sensor types 67
 - what they sense 66–67
 - where to use 65–66
 - efficiency, effect on 60
 - optimum 60
 - problems related to 60–61, 61
- Ammonia**
 - in absorption cooling 1325
 - in cooling storage systems 420
 - superheat 387
- Analog controls.** *See* Controls, characteristics of
- ANSI ballast codes 1075**
- Antarctic Circle 1285**
- Anticipators, thermostat**
 - adjust to minimize standby losses **804**
 - description 1379
- Antifreeze**
 - in hydronic systems 568
- Arc, in lighting**
 - definition 1459
 - in fluorescent lighting 1459–1460
 - in HID lighting 1471
- Arc lighting.** *See* Lighting, arc
- Arctic Circle 1285**
- Argon**
 - in fluorescent lamps 1461–1464
 - in high-pressure sodium lamps 1478
 - in incandescent lamps 1451
 - in low-pressure sodium lamps 1479
 - in mercury vapor lamps 1475
 - in metal halide lamps 1476
- ASHRAE Standard 62-89 (ventilation) 522, 528, 529, 530**
- ASHRAE Standard 90.** *See* Efficiency codes, laws & standards
- Astragal 810**
- Astronomical timeclocks 1100–1101, 1200–1201**
- Attic insulation.** *See* Insulation, for attics
- Attic ventilation.** *See* Ventilation, for attics
- Awnings 920–921**
- Azeotropes 1335**
- Azimuth, how to determine 927**

B**Back check** 811**BACnet** 1226**Baffle plate** 577–578**Bagasse**

fuel properties of 1247

Balconies, for shading 919**Ballast efficiency factor (BEF)** 1061**Ballast factor** 1060–1061**Ballasts, lighting.** *See* Lighting, fluorescent; Lighting, high intensity discharge**Barometric dampers.** *See* Draft, combustion: draft regulators**Baseboard radiators.** *See* Radiators**Bellows traps.** *See* Steam traps**Betz Coefficient (wind energy)** 1275**Biomass combustion 1281–1282**

applications 1281, 1281–1282

availability 1281

economics 1281

energy content 1281

environmental issues 1281–1282

equipment 1281

safety issues 1281

Bipolar junction transistor 1355**Black body** 955**Bleed, cooling tower.** *See* Water treatment, cooling water**Blinds, window.** *See*

Daylighting; Shading, to reduce cooling load

Blowdown, boiler 148

& total dissolved solids (TDS) 148–149

automatic controls for **157–158**

bottom blow 154–155

definition 141, 153

effects of improper control 153–154

energy wasted by 155

hazards 155

heat recovery from. *See* Heat

recovery: from blowdown

how to calculate rate 155

optimum control **153–156**

of bottom blow 156

of top blow 155–156

surface blow 154–155

top blow 154–155

when shutting down boiler 118

Blower doors 1384–1385**Boiler capacity ratings 1294–1295****Boiler efficiency testing 43**

assumptions involved 46–47

definition 44

errors 46–47

from extraneous air 51, 51–52

from sensing wrong gases 52

from steam leaks 52

from unburned fuel 48

in equipment 48, 49–51

flame appearance 48

how it works 46–47

how often to repeat 53

how to do 45–46, 51–52

load conditions 52

preparing the boiler 52–53

with air preheaters 52

with economizers 52

with flue gas recirculation 52

limitations 44–45, 46–47

reasons for 43, 44

test equipment

air casing pressure gauges 55

BTU meters 55

calibration **57**

chemical 49, 50

digital 56

displays 55–56

electronic 49–51

for carbon dioxide 48, 49–50

for carbon monoxide 50–51

for oxygen 49–50

for smoke density 50–51

fuel flowmeters 54–55

fuel pressure gauges 55

fuel quantity indicators 55

Fyrite 49

how to select 49–51

install permanent **54–56**

Orsat analyzer 49

pollutant sensors 54

recorders 55–56

smoke opacity sensors 54

steam meters 55

thermometers, flue gas 51, 54

thermometers, fuel oil 55

test for boiler defects 48

test for carbon dioxide

how to do 45–46

test for carbon monoxide 48

test for incomplete combustion 48

test for oxygen

check with carbon dioxide test 47–48

how to do 45–46

why better than carbon dioxide

test 47

test for smoke opacity 48

test for specific pollutants 48–49

training for **58****Boiler feedwater systems**

components 140–141

deaerating tank

for oxygen removal

141, 144, 146

functions 140–141

in feedwater system 146

for steam turbines 141

functions 137

pump characteristics 1342, 1344

Boiler horsepower (definition) 1294–1295**Boiler loading, optimum 34–37**automatic controls for **38–39**

how to select 39

other functions 39

programming 39

where to consider 38

energy saving 34–35

how to calculate 35

start-stop sequence 35–37

Boiler plant layoutcross connect boiler plants **233–235**

benefits 233

boiler sequencing 234

capacity, overall increase 234

compatibility of the plants 233

condensate return 234

disadvantages 233

feasibility factors 235

piping costs 234

pumping costs 234

reliability improvement 234

install lead boiler **226–229**

cost 227

energy saving 226

feasibility factors 228

install local heaters to allow shut-

down **230–231**

feasibility factors 230–231

install local high-pressure boilers

232

overhead costs, effect on 228

Boiler plant maintenance

air preheaters 128

air-fuel ratio controls **69–70**blowdown. *See* Blowdown, boiler

boiler leaks 185

burners. *See* Burner systems, fuel

- fireside cleaning
 - & air-fuel ratio 111
 - how often 110
 - how to minimize fouling 111
 - how to monitor fouling 110
 - methods of cleaning 110
 - turbulators, interference from 135
 - types of fouling 110
 - when to clean 111
- leakage, monitoring **182**, 183–184
- leakage, repair **183–186**
 - how to find leaks 184–186
 - how to repair joints 185–186
 - savings from 183
- soot blowing. *See* Soot blowers
- water treatment. *See* Water treatment, boiler water
- waterside cleaning **116–117**
 - & water treatment 117
 - how to minimize fouling 117
 - methods 116–117
 - types of fouling 116
 - when to clean 116
- when shutting down boiler **118**
- Boiler plant, minimize operation 20–21**
 - auxiliary equipment 21, **31–32**
 - control conditions 32
 - energy saving 32
 - interlock with boilers **33**
 - spare pumps **34**
 - by annunciator panel **27**
 - by clock control **22**
 - by optimum-start control **23–24**
 - description 23
 - how to install 24
 - low-temperature protection 23–24
 - methods 24
 - where to use 23
 - by outside air temperature **25–26**
 - energy savings 25–26
 - how to install 26
 - where to use 25
 - coordinate with cooling controls 21
 - cycling limitations 33
 - energy saving 20
 - in cross connected plants 234
 - minimum shutdown intervals 20–21
 - placards 21
 - where to control 20
- Boiler steam pressure, minimize 40–42**
 - benefits 40
 - hazards 41
 - install local high-pressure boilers **232**
 - limitations 41
 - staffing reduction 40, 41–42
 - steam metering error 41
- Boilers**
 - air preheaters. *See* Air preheaters, boiler
 - air-fuel ratio. *See* Air-fuel ratio
 - auxiliary equipment. *See* Boiler plant equipment management: auxiliary equipment
 - burners. *See* Burners, fuel
 - cast iron sectional 1293–1294
 - & water treatment 145
 - coil boilers 1293
 - combustion chamber. *See* Burner systems, fuel
 - condensate. *See* Condensate systems
 - condensing 1294
 - draft. *See* Draft, combustion
 - economizers. *See* Economizers, boiler; economizers, boiler
 - efficiency characteristics 34–35
 - efficiency testing. *See* Boiler efficiency testing
 - electric 1294
 - fans. *See* Burners, fuel
 - feedwater. *See* Boiler feedwater systems
 - firetube 1289
 - construction 1289
 - mud drums 154
 - pressure limitations 1289
 - fluidized bed 86, 1250
 - for superheated steam 1291
 - fuel selection. *See* Fuel selection, boilers
 - lead boiler. *See* Boiler plant layout: install lead boiler
 - leaks in 185
 - maintenance. *See* Boiler plant maintenance
 - effect of fuel choice 1250
 - operation. *See* Boiler plant equipment management
 - soot blowers. *See* Soot blowers
 - standby losses. *See* Standby losses, combustion equipment
 - turbulators for. *See* Turbulators, for firetube boilers
 - types of boilers **1289–1295**
 - water treatment. *See* Water treatment, boiler water
 - watertube 1289
 - construction 1289–1293
 - steam drum 1293
 - water circulation 1291–1293
- Brightness.** *See* Lighting, design issues
- BTU meters.** *See* Heat meters
- Bucket traps.** *See* Steam traps
- Buffer gas.** *See* Lighting, fluorescent
- Burner systems, fuel 71**
 - air-fuel ratio. *See* Air-fuel ratio
 - characteristics 78–80
 - air pollution 79
 - auxiliary energy requirement 79
 - combustion chamber insulation 79
 - cost 80
 - draft requirements 79
 - efficiency 78
 - excess air requirement 78
 - flame pattern 78, 86–87
 - maintenance requirements 79–80
 - multi-fuel capability 80
 - standby losses 79. *See also* Standby losses, combustion equipment
 - turndown ratio 79
 - combustion chamber, matching 79, 86–87
 - efficiency
 - & modulation 35
 - fan drive, install variable-output **90–92**
 - energy saving 90–91
 - how to install 91–92
 - how to select 91
 - where to consider 90
 - firing rate, reduce **75**
 - flame appearance 48
 - install efficient **78–88**
 - maintenance **72–74**
 - motors **89**
 - multi-fuel 80, 85
 - oxygen trim systems. *See* Air-fuel ratio: automatic controls
 - pilot flame, upgrade to electrical **89**
 - problem diagnosis 73
 - problems related to 60–61, 73
 - air casing leakage **74**
 - air pollution 60–61
 - clogged burner 73
 - dirty burner 73
 - efficiency loss 73
 - explosion hazard 61
 - fireside fouling 61
 - flame instability 61, 73
 - incomplete combustion 61
 - linkages loose 73
 - refractory damage 73, 86–87

smoke 73
 soot in boiler 73
 vibration 73
 recirculation of flue gas 79
 types of burners 81–86
 coal, pulverized 85
 dual-fuel 85
 flame retention 79
 fluidized bed 86
 gas, atmospheric 81–83
 gas, power, modulating 83
 gas, power, single-stage 83
 gas, power, staged 83
 oil, air-atomizing 84
 oil, pressure-atomizing, modulating 83–84
 oil, pressure-atomizing, multi-stage 83
 oil, pressure-atomizing, single-stage 83
 oil, rotary cup 84–85
 oil, steam-atomizing 84
 retention head 79
 stoker 85–86
 whether to upgrade 87–88

C

Calcium, in boiler water 144, 145–146
Candela (definition) 1423–1424. *See also* Lighting, measurements
Candlepower (definition) 1423–1424. *See also* Lighting, measurements
Capacitors, power factor correction
 problems with VFD's 1366, 1369–1370
Capillary tube refrigerant distributors 1318
Carbon dioxide test, combustion. *See* Boiler efficiency testing
Carbon monoxide
 sensors for. *See* Air-fuel ratio: automatic controls
Carbon tax 1250
Carnot efficiency
 for cooling 1302–1303
Carryover, in boilers. *See* Water treatment, boiler water
Cast iron boilers. *See* Boilers: cast iron sectional
Catalysts
 in fuel oil 178
Ceiling, suspended. *See* Insulation, for suspended ceiling

Cellulose insulation. *See* Insulation, types: cellulose
Certification. *See* Efficiency codes, laws & standards
Certified Ballast Manufacturers (CBM) 1063
CFC refrigerants. *See* Refrigerants
Changeover, heating/cooling. *See* Air handling systems, VAV single-duct: terminals, heating/cooling changeover, install
Chelants, in boiler water 146–148
Chilled water pumping. *See* Pumps, centrifugal: throttling output
Chilled water pumping. *See* Pumping, variable-flow, chilled water
Chilled water temperature, maximize 264–265, 265
 by manual reset 265
 compromise with fan power 264
 compromise with pump power 264
 potential for 264
 when turning off CHW pumps 259
Chiller load, how to measure 242
Chiller loading, optimize 240–242, 243–244
 absorption/compression systems
 for modulating chillers 241
 for multi-stage chillers 240
 for single-stage chillers 240
 how to measure load 242
 load setting methods 241
 with energy management system 243
 with scheduling controller 243–244
 how to select 243
 where to consider 243
Chillers. *See* Cooling, by type
Chimney effect
 avoiding air leakage from. *See* Section 6
 cause of boiler draft problem 100–101
 explanation of 1383–1385
 in elevator shafts 872
Chlorine
 in ozone depletion 1335–1336
 in refrigerants. *See* Refrigerants
Chlorofluorocarbon refrigerants. *See* Refrigerants
Chromaticity 1442–1443
CIE Chromaticity 1442–1443
Clean Air Act
 & refrigerants 1333
Clearance volume
 definition 1305–1306
 in reciprocating compressors 1309

Clerestory windows
 light shelves for 1005
Clock controls 1199–1204
 astronomical 1200–1201
 backup features 1202
 cycle timers 1200
 ease of use 1202
 electrical features 1201
 for air handling systems. *See* Air handling systems, minimize operation
 for boiler plant. *See* Boiler plant, minimize operation
 for heating & cooling units. *See* Heating & cooling units, minimize operation
 for hot water recirculation 493–494
 for lighting 1098–1099
 astronomical controls 1100–1101
 with photocontrols, exterior lighting 1102
 with photocontrols, interior lighting 1105
 installation 1204
 optimum-start 1201
 output signals 1201
 overrides 1203–1204
 physical features 1202
 programmable thermostats 1202
 scheduling features 1199–1201
Closed-loop controls 1381
Coal
 environmental protection costs 1250
 fuel properties of 1247–1249
Coanda effect 594
 in air diffusers 626–627
Coefficient of performance. *See* Efficiency ratings, cooling. *See also* type of equipment
Cogeneration 1329–1330
Cogging (variable-frequency drives) 1364
Coil boilers. *See* Boilers: coil boilers
Coils, heating & cooling
 control valves
 in variable-flow systems 323
 control valves, bypass 255–257
 how to eliminate 257
Color
 definition 1434
 exterior surfaces, to reduce heat gain. *See* Shading, to reduce cooling load: by surface finish
 interior surfaces. *See* Lighting, reflective space surfaces
 interior surfaces, to enhance daylighting 996–998, 1006

- interior surfaces, to reduce lighting power **1116–1118**
- & fixture layout 1116
- diffuse or specular? 1117–1118
- energy saving 1116
- esthetics 1117
- of lamp light. *See* Lighting, by type; Lighting, design issues: lamp characteristics
- Color printing** 1434
- Color rendering.** *See* Lighting, design issues
- Color rendering index (CRI)**
 - definition 1441
 - of lamp types. *See* Lighting, by type
- Color television** 1434
- Color temperature (lamps).** *See* Lighting, design issues: lamp characteristics
- of lamp types. *See* Lighting, by type
- Color vision.** *See* Vision, human: color
- Combustion efficiency test.** *See* Boiler efficiency testing
- Commodity charges, electricity** 1253
- Commutation, in variable-frequency drives** 1355
- Commutator (DC motor)** 1370–1371
- Compact fluorescent lamps.** *See* lighting, fluorescent: compact fluorescent units
- Compression ratio, cooling compressors**
 - efficiency, effect on 1306
 - fixed vs. variable 1306
- Compressor drivers** 1315–1317
 - diesel engines 1317
 - electric motors 1315–1316
 - efficiency 1316–1317
 - hermetic 1315–1316
 - internal vs. external 1315–1316
 - open drive 1315–1316
 - semi-hermetic 1315
 - gas turbines 1317
 - how to select 1317
 - natural gas engines 1317
 - steam turbines 1317
- Compressors, cooling, centrifugal** 1307–1309
 - efficiency 1307–1309
 - false loading 1308
 - hot gas bypass 1308
 - impellers
 - diameter 1309
 - gear-driven 1309
 - number of 1309
 - speed 1309
 - in lead chillers 358
- output modulation 1306, 1308–1309
 - condensing temperature, effect on 386
 - inlet guide vanes 1308
 - operating temperature limitations 1309
 - variable-speed drive 335–336, 1308–1309
 - with multiple compressors 1308
- retrofit variable-speed drive 335–336
 - energy saving 335–336
 - limitations 335–336
 - potential chiller damage 336
 - surge limitations 1308
- Compressors, cooling, in general**
 - efficiency factors 1304–1306
 - clearance volume 1305–1306
 - compression ratio 1306
 - gas flow 1305
 - internal leakage 1305
 - interstage heat transfer 1305–1306
 - output modulation 1306
 - refrigerant type 1305
- motors, replace with more efficient **332**
 - hermetic motors 332
 - with variable-frequency drives 332
- replace with efficient **333–334**
 - how to select 333
 - matching to chiller 333
 - reducing capacity 334
 - updating refrigerant 334
 - when to consider 334
- Compressors, cooling, reciprocating** 1309–1310
 - efficiency 1309–1315
 - in lead chillers 358
 - output modulation 1306, 1310–1315
 - suction cutoff 1310
 - unloading cylinders 1310
 - variable-speed drive 1310
 - with multiple compressors 1310
- Compressors, cooling, screw** 1310–1313
 - compression ratio 1313
 - economizer 1313
 - in lead chillers 358
 - oil heat recovery 386–387
 - oil injection 1312–1313
 - output modulation 1313
 - single-screw 1310–1313
 - twin-screw 1310–1313
- Compressors, cooling, scroll** 1313–1314
 - construction 1313–1314
 - efficiency 1314
 - in lead chillers 358
 - output modulation 1306, 1314
- Compressors, cooling, vane** 1314–1315
- Computer programs**
 - energy analysis. *See* Energy analysis
 - computer programs
 - load calculation 1240
- Condensate (of steam)**
 - definition 137–141
 - handling. *See* Condensate systems
 - treatment. *See* Water treatment, boiler water
- Condensate subcooling** 1321
- Condensate systems**
 - & water treatment 165
 - atmospheric 138–140
 - closed 138–140
 - components 138–140
 - for cross connected plants 234
 - functions 137
 - high-pressure 138–140
 - insulation 214
 - makeup water 137, 138
 - maximize condensate return **163–165**
 - heat recoverable 163–164
 - why to return 163
 - motors, high-efficiency **171**
 - pumping high-temperature condensate 165
 - vacuum. *See* Vacuum condensate systems
- Condenser waterside cleaning** **276–277, 277–278**
 - cooling tower water treatment. *See* Water treatment, cooling tower
 - when to clean 276
 - with automatic tube cleaner **277–278**
 - maintenance for 278
- Condensers, cooling system**
 - air-cooled condenser 1302
 - auxiliary. *See* Heat recovery, from cooling equipment: by auxiliary or double-bundle condenser
 - cleaning air-cooled condensers 754, **765**

- cleaning water surfaces. *See* Condenser waterside cleaning
- condensate subcooling 1321
- double-bundle. *See* Heat recovery, from cooling equipment: by auxiliary or double-bundle condenser
- evaporative condensers 1302
- heat transfer design 1320
- fouling factor 1320–1321
- methods of limiting cooling 269–270
- temperature limits, minimum 268–269
- temperature, optimize. *See* Condensing temperature, optimize
- Condensing boilers.** *See* Boilers: condensing
- Condensing furnaces.** *See* Direct-fired heating units
- Condensing temperature, optimize 267–270, 270–271, 272–273**
- by automatic reset 272–273
- control options 272
- how to program 272
- by manual reset 270–271
- cautions 267–268
- control accuracy 270
- energy saving 268
- how to calculate 269
- in chiller heat recovery. *See* Heat recovery, from cooling equipment
- in lead chillers 358
- in split systems 768–769
- minimum temperature limits 268–269
- with heat recovery storage 403
- Conduction, of heat.** *See* Heat, in general: how heat moves
- Cone cells (vision)** 1429, 1434
- Control of equipment operation**
- for air conditioners. *See* Heating & cooling units, minimize operation
- for air handling systems. *See* Air handling systems, minimize operation
- for boiler plants. *See* Boiler plant, minimize operation
- for cooling plant. *See* Cooling plant, minimize operation
- for direct-fired heating units. *See* Heating & cooling units, minimize operation
- for fan-coil units. *See* Heating & cooling units, minimize operation
- for furnaces. *See* Heating & cooling units, minimize operation
- for heat pumps. *See* Heating & cooling units, minimize operation
- for heating & cooling units. *See* Heating & cooling units, minimize operation
- for lighting. *See* Lighting, control of
- for radiators. *See* Heating & cooling units, minimize operation
- for unit heaters. *See* Heating & cooling units, minimize operation
- for water heating. *See* Water heating for water pumping. *See* Pumping, service water pressure; Pumping, service water recirculation
- Control signal polling 1227**
- signal discriminators 1227
- using energy management computer for 1227
- Controls, characteristics of 1377–1381**
- analog 1377, 1381
- analog-to-digital converter 1377
- anticipators 1379
- automatic reset 1379–1380
- closed-loop 1381
- differential 1378
- digital 1377, 1381
- direct-acting 1377–1378
- drift 1379
- droop 1379
- electric 1377
- feedback 1381
- fiber optic 1377
- heat/cool changeover. *See* Air handling systems, VAV single-duct: terminals, heating/cooling changeover, install
- hysteresis 1379
- infrared 1377
- offset 1379
- on-off 1377, 1378–1379
- open-loop 1381
- pneumatic 1377
- proportional 1377, 1379–1380
- proportional-integral (PI) 1379–1380
- proportional-integral-derivative (PID) 1380
- reverse-acting 1377–1378
- sensitivity 1378
- setpoints 1377
- signal offset relays 603
- stability 1378, 1379
- staged 1378
- two-position 1378–1379
- Convection**
- definition 1388
- Convectors.** *See also* Radiators (Same Measures apply.)
- definition 719
- Cooling, absorption 1323–1330**
- comparison with compression cooling 1329
- components of 1323–1325
- absorber 1323–1324
- ammonia 1325
- concentrator 1324
- condenser 1324
- corrosion inhibitors 1325
- distiller 1324
- economizer 1327–1328
- evaporator 1323
- float valve 1325
- generator 1324
- heat exchanger 1324–1325
- lithium bromide 1325
- orifice 1325
- purge unit 1325
- refrigerant pump 1325
- solution pump 1325
- crystallization 1326–1327
- direct-fired 1326
- efficiency 1325–1326. *See also* Efficiency ratings, cooling chilled water temperature, effect of 1327
- condenser temperature, effect of 1327
- economizer 1327–1328
- effect of fuel heat value 1297–1298
- number of stages, effect of 1325–1326
- part-load 1327–1328
- salt concentration, effect of 1327–1328
- externally fired 1326
- heat recovery from 387
- heating capability 1328–1329
- how it works 1323
- in cogeneration systems 1329–1330
- in combination systems 1329–1330
- lead chiller, unsuitable as 358
- number of stages 1325–1326
- operating temperatures
- capacity, effect on 1328
- efficiency, effect on 1327
- number of stages 1325
- two-stage 1325–1326
- Cooling, compression 1299–1321**
- components of system 1300–1301
- accumulator 1301
- compressor 1300. *See also* Compressors, cooling, by type

- condenser 1300–1301. *See also*
- Condensers, cooling system
- crankcase heater 1301
- evaporator 1300. *See also*
- Evaporators, cooling system
- expansion valve 1301
- float valve 1301
- orifice 1301
- purge unit 1301
- receiver 1301
- refrigerant metering device 1301
- turbine, energy recovery 1301
- efficiency. *See also* Efficiency ratings, cooling
- Carnot efficiency 1302–1303
- compressors, effect on 1303
- maximum theoretical 1302–1303
- operating temperatures, effect of 1302–1303
- refrigerants, effect on 1303
- how it works 1299–1300
- operating temperatures
- capacity, effect on 1304
- chilled water, optimum. *See* Chilled water temperature, maximize
- condensing, minimum 268–269, 1306
- condensing, optimum. *See* Chilled water temperature, maximize
- efficiency, effect on 1302–1303
- factors that determine 1303–1304
- refrigerants for 1300, **1331–1338**
- system layouts 1302
- air-cooled condensing unit 1302
- direct expansion 1302
- hydronic 1302
- split system 1302
- Cooling cycle, definition** 1299
- Cooling plant layout**
- cross connect chiller plants 364–366
- improve overall capacity 365
- improve overall reliability 365
- optimize overall control 365
- pipng design issues 364–365
- reduce overall operating cost 365
- efficient equipment sizing **357–360**
- auxiliary equipment load, minimize 359
- energy waste related to 355–356
- how to select chiller size 358–359, 359
- install local cooling units to allow shutdown **361–363**
- appearance 362
- condenser cooling 362
- cost saving 362
- efficient control 362
- electrical power for 362
- energy saving 361–362
- how to distribute 362
- how to select local units 362
- installation issues 362
- noise 362
- relative efficiencies 361–362
- space requirements 362
- Cooling plant, minimize operation** **245, 246, 247–248, 249, 250**
- by annunciator panel **250**
- by clock control **249**
- by optimum-start control **249**
- by outside air temperature or enthalpy **247–248**
- how to install sensor 247–248
- where to consider 247
- whether to use temperature or enthalpy 247
- by sensing cooling load **246**
- energy saving 245
- heat rejection equipment. *See* Heat rejection equipment, minimize operation
- pumps, chilled water **253–259**
- dangers 254
- energy saving 253–254
- how to control 256–257
- how to eliminate bypass valves 257
- isolate idle evaporators 257–258
- use temperature reset 259
- where to consider 253–254
- with cooling coil bypass valves 255–257
- with return water temperature control 258
- with system bypass valve 254–257
- pumps, spare **260**
- sump heaters, compressor **261**
- vs. local cooling unit control 245
- Cooling, solar.** *See* Solar cooling
- Cooling system leakage**
- how to find refrigerant leaks 340–341
- by pressurizing system 352
- dyes in oil 340
- halocarbon torch 340
- ionization detector 340
- odor 340
- soap bubbles 340
- visible corrosion 340
- preventing air leakage into idle chillers **352–353**
- by inert gas pressurization 352
- by warming refrigerant 352
- preventing water leakage into idle chillers **354**
- symptoms of leakage 340
- types of leaks
- air entry into system 338–339
- loss of refrigerant 338
- water entry into system 339
- water vapor entry into system 338–339
- where leaks occur 339–340
- Cooling systems.** *See* Cooling, absorption; cooling, compression
- Cooling tower, direct cooling with**
- by strainer cycle
- system cleaning 279
- Cooling towers.** *See also* Heat rejection equipment
- COP (coefficient of performance).** *See* Efficiency ratings, cooling
- Correlated color temperature (lamps)**
- definition 1441–1443
- Cove lighting** 1116, 1132, 1136–1138
- Crankcase heaters, compressor.** *See* Sump heaters, compressor
- Crest factor** 1061–1062, 1075
- Crystallization, in absorption cooling** 1326–1327
- CSI (current source inverter) drives.** *See* Drives, variable-frequency
- Current source inverter (CSI) drives.** *See* Drives, variable-frequency
- CW/CWA ballasts, for HID lighting** 1474–1475
- Cycle timers** 1200
- Cycloconverter** 1355

D**Damperless multizone systems** 653**Dampers**

- boiler draft regulating. *See* Draft, combustion: draft regulators
- flue. *See* Flue dampers, automatic for air handling systems. *See* Dampers, control
- in burner systems. *See* Burner systems, fuel
- in heat rejection equipment 296

Dampers, control 532–533

- & freeze protection 571
- & stratification 576
- arrangements in air handling systems 498, 522–524, 523–524, 532–533
- control accuracy 533
- energy waste by 524, 533, 548
- leakage 533, 548
- need for tight closing 534

Dampers, infiltration 533, 534**Darlington transistor** 1355**Daylighting, by light pipes** 966–

- 978.** *See also* Daylighting, design issues
- advantages 966–967
- diffusion, need for 970–971
- disadvantages 966–967
- electric lighting, compatible types 976
- electric lighting, control of 975–976
- energy saving 967
- glare 971
- light loss in pipe 977
- materials 973
- sun trackers 977
- where to use 966–967

Daylighting, by light shelves 1000–

- 1005.** *See also* Daylighting, design issues
- components 1000–1002, 1003–1005
- energy saving 1000
- explaining to occupants 1005
- exterior shading, specialized 1004–1005
- layout 1003–1005
 - electric lighting 1004
 - shading, exterior 1004–1005
 - shading under shelf 1004
 - shelf height 1004, 1005
 - shelf shape 1004
 - with clerestory windows 1005
- light distribution pattern 1002–1003

- safety issues 1005
- shelf cleaning 1005
- where to consider 1000

Daylighting, by skylights 966–

- 978.** *See also* Daylighting, design issues
- advantages 966–967
- area required 967–968
- condensation 971–973
- configurations 973–975
- diffusers, install **979–982**
 - condensation, avoiding 981
 - glare, avoiding 981
 - how to use 979–980
 - insulation benefit 981
 - materials 981
- diffusion, need for 970–971
- disadvantages 966–967
- electric lighting, compatible types 976
- electric lighting, control of 975–976
- energy saving 967
- glare 971
- heat loss 971–973
- layout 969–970
- materials 973
- water leakage, preventing 975
- where to use 966–967

Daylighting, by translucent roof & walls 983–993. *See also* Day-

- lighting, design issues
- & conductive heat loss 991–992
- & solar heat gain 991
- area 989
- design for durability 992
- design for replacement 992
- energy saving 984–985
- glare, avoiding 989–991
 - from roof installations 991–993
 - from wall installations 989–990
- materials, extruded plastic 987–989
 - appearance 989
 - diffusion 988
 - fire characteristics 989
 - insulation value 988
 - light transmission 988
 - service life 988
 - structural properties 987
 - view 988
- materials, fiber-reinforced plastic 985–987
 - appearance 987
 - construction 985–986
 - diffusion 987
 - dimensions 986
 - fire characteristics 987

- insulation value 987
- light transmission 987
- service life 986–987
- view 987

- water leakage, avoiding 992
- where to consider 983–984

Daylighting, by window diffusers

- 994–999.** *See also* Daylighting, design issues
- & solar heat gain 998–999
- condensation, avoiding 998
- diffuser materials 995–996
- energy saving 994
- glare, avoiding 994–995
- how to install 995–996
- insulation value, exploiting 998
- view, effect on 999
- where to consider 994

Daylighting, design issues 1405–

- 1413.** *See also* Lighting, design issues; Solar heating, passive: design issues; Sunlight, characteristics
- avoiding visual desensitization 1410
- brightness variations 1410
- climate 1412
- cooling load 1412
- electric lighting. *See also* Section 9
 - circuit layout 1107
 - control issues 1410–1412
 - dimming, fluorescent **1066–1068**
 - dimming, HID **1079–1080**
 - lamp types 1410
- energy available in sunlight 914
- glare 1406
- glazing area 950, 1412
- glazing insulation value 1412–1413
- glazing treatments 1412
- intensity 1406
- light pipes 1412–1413. *See also* Daylighting, by light pipes
- needed technology 1412–1413
- passive solar heating effect 1412–1413
- penetration 1405, 1406–1410
- problems 1405–1406
- reflective interior, exploiting **1006**
- sunlight, characteristics **1283–1287**
- tree shading, effect of 961
- veiling reflections 1406
- visual quality 1406

Deadband

- in air handling systems. *See* Air handling systems, by type
- thermostats. *See* Thermostats: deadband

- Deaerating feedwater tanks.** *See* Boiler feedwater systems
- Deballasting.** *See* Lighting efficiency improvements, fluorescent: lamps & ballasts, remove excess
- Dehumidifiers**
to augment mechanical cooling 550
- Delamping.** *See* Lighting efficiency improvements, fluorescent: lamps & ballasts, remove excess
- Demand charges, electricity.** *See* Electricity pricing: demand charges
- Demulsifiers**
in fuel oil 179
- Deregulation of utilities**
effect on thermal storage 411
- Desuperheater, cooling machine.** *See* Heat recovery, from cooling equipment: by desuperheater
- Detergents, low-temperature** 461
- Dial timers.** *See* Timed-turnoff switches
- Diffusers**
for skylights. *See* Daylighting, by skylights
for windows. *See* Daylighting, by window diffusers
- Digital controls**
energy management systems. *See* Energy management control systems
- Dimmers, lighting.** *See* Lighting, fluorescent; Lighting, HID; Lighting, incandescent
- Direct contact heat exchanger.** *See* Economizers, boiler: water spray
- Direct expansion cooling systems**
definition 1302
- Direct-current motors.** *See* Drives, direct-current (DC)
- Direct-fired heating units**
anticipators, adjust 804
efficiency ratings 801
flue dampers for. *See* Flue dampers, automatic
flue gas condensing 800
install efficient 799–801
efficiency characteristics 799–800
flue gas condensing 800
multi-fuel 801
when to replace 799
maintenance 798–799
multi-fuel 801
- Disc traps.** *See* Steam traps
- Discotheques** 1118
- Discriminators, control signal.** *See* Control signal polling
- Dispersants**
in boiler water 148
in fuel oil 179
- Dock levelers** 856
- Dock seals 854–857**
damage during loading 856–857
dock doors, compatibility 857
durability 857
ease of installation 857
ease of repair 857
height change during loading 856
pressure on wall 857
selection issues 856–857
types of dock seals 854–856
vehicle alignment with 857
vehicle dimensions 856
vehicle doors, type of 856
vehicle guides 857
vehicle tilt 856
- Door closers, for personnel doors 811–812**
desirable features 811
how to install 811–812
- Door operators, powered**
for large exterior doors 830–832, 835
how to connect to door 830–831
how to control 831–832
instructions for 832
types of operators 830
for personnel doors 812–813 & vestibules 812–813
types 812
- Door switches**
for lighting control 1113
- Doors**
abandoned, sealing 823
automatic. *See* Door operators, powered
bi-fold. *See* Doors, large exterior
buck. *See* Doors, personnel
closers. *See* Door closers
fabric. *See* Doors, impact
folding horizontally. *See* Doors, large exterior
folding vertically. *See* Doors, large exterior
freezer. *See* Doors, quick-acting powered
garage. *See* Doors, large exterior; Doors, quick-acting powered
hangar. *See* Doors, large exterior
horizontal roll-up. *See* Doors: quick-acting
acting
impact. *See* Doors, impact
industrial. *See* Doors, large exterior; Doors, quick-acting powered
loading dock. *See* Doors, large exterior; Doors, quick-acting powered
material handling. *See* Doors, quick-acting powered
operators. *See* Door operators, powered
panel. *See* Doors, large exterior
personnel. *See* Doors, personnel powered. *See* Door operators, powered; Doors: revolving; Doors, quick-acting powered
quick-acting. *See* Door operators, powered; Doors, quick-acting powered
revolving. *See* Doors, revolving roll-up. *See* Doors, large exterior; Doors, quick-acting powered
roll-up strip curtain. *See* Doors, quick-acting powered; Doors, strip curtain
seals for. *See* Weatherstripping segmented. *See* Doors, large exterior
sliding. *See* Doors, large exterior
storm. *See* Doors, storm
strip curtain. *See* Doors, strip curtain
swing. *See* Doors, impact; Doors, large exterior; Doors, personnel
vehicle. *See* Doors, large exterior; Doors, quick-acting powered
vertical roll-up. *See* Doors: quick-acting
acting
vestibules for. *See* Vestibules
weatherstripping for. *See* Weatherstripping
- Doors, impact**
comparison to other types 839
fabric impact doors 842–843
characteristics 839, 842
signage for 842
rigid impact doors 843–845
characteristics 839, 843
how to select 843
signage for 845
where to consider 839–840

Doors, large exterior

clearance when operating 836
 dead space required 835–836
 ease of installation 838
 ease of operation 836–837
 install efficient **833–838**
 insulation 835
 maintenance **826**
 man doors in 837–838
 operators for 835
 safety features 837
 security 838
 selection issues 834–838
 speed of operation 836
 strength 837
 types of large doors
 bi-fold 833
 folding horizontally 833
 folding vertically (bi-fold) 833
 overhead segmented 833–834
 overhead single-panel 833
 roll-up 833
 sliding 833
 swinging 833–834
 weatherstripping 834–835
 which type is best 838
 windows in 837–838

Doors, personnel

closers. *See* Door closers
 install high-efficiency **814**. *See also*
 Doors, revolving
 maintenance **808**
 weatherstripping. *See* Weatherstrip-
 ping: for personnel doors

Doors, quick-acting powered 846–853

characteristics 839
 comparison to other types 839
 condensation, preventing 851–852
 drippage 852
 durability 848–849
 ease of repair 849–850
 frost, preventing 851–852
 guards for 853
 hazards 850–851
 impact resistance 849–850
 infiltration through 847–848
 installation issues 852–853
 insulation 848
 maintenance, need for 853
 roll-up strip curtains 841
 safety features 850–851
 security 852
 selection issues 846–852
 sensors for opening & closing 852–853
 signage for 853

speed of operation 846–847
 types of quick-acting doors
 folding horizontally 846
 freezer 846
 overhead sectional 846
 roll-up horizontally 846
 roll-up vertically 846
 weatherstripping 847–848
 where to consider 839–840
 wind resistance 848

Doors, revolving 815–816

need for standby door 816, 817
 signage for **817**
 where to consider 815–816

Doors, storm 818

advantages 818
 disadvantages 818
 features to seek 818–819
 installation 819
 where to consider 818

Doors, strip curtain 840–841

characteristics 839, 840
 comparison to other types 839
 how to install 840–841
 maintenance 841
 powered roll-up strip curtains 841
 where to consider 839–840

Downlights

energy wasted by 1033
 install focussing extensions in **1039**
 install reflective inserts in **1038**
 lamps for
 ellipsoidal reflector incandescent
 1034
 focussing **1033–1035**
 screw-in fluorescent **1025–1030**, 1034
 vertical-filament incandescent
 1033
 remove excess **1132**
 replace **1135–1136**

Draft, combustion

& burner type 79
 adjusting **94–98**
 by convection 94
 by fans 94
 correcting problems **99–101**
 building chimney effect 100
 defect in draft regulator 99
 excessive flue draft 99
 fan pressure in boiler room 101
 inadequate flue draft 99
 inadequate outside air 100–101
 soot obstruction 101
 wind effects on boiler room 100
 wind effects on flue 99–100
 definition 94–95

draft regulators 95–97
 barometric dampers 96
 draft hoods 96
 motorized dampers 96–97
 variable-output fan 97
 how to measure 97–98
 overfire draft 97
 purposes 94
 stack draft 98
 when to check 98

Draft, in air distribution 620**Draperies**

avoid heat trapping against wall
 by fan-coil units **745–747**
 by induction terminal units **699**
 by radiators & convectors **727–728**
 insulation value 727
 to reduce cooling load 931

Drip trap. *See also* Steam traps
 definition 188

Drivers, for cooling

compressors. *See* Compressor
 drivers

Drives, direct-current (DC) 1370–1373

advantages 1371–1372
 applications. *See* Drives, variable-
 speed
 bypass, emergency 1372
 efficiency 1371
 features to consider 1373
 how they work 1371
 maintenance 1372
 motors, direct-current 1370–1371
 commutator 1370
 how they work 1370–1371
 windings 1370
 power factor 1372
 problems and solutions 1372–1373
 speed precision 1371
 torque handling ability 1371–1372
 turndown ratio 1371

Drives, eddy current clutch 1374

applications. *See* Drives, variable-
 speed
 efficiency 1374
 how they work 1374
 mounting methods 1374
 turndown ratio 1374

Drives, multi-speed motor. *See also*

Motors, AC induction: multi-
 speed
 applications. *See* Drives, variable-
 speed
 for air handling system fans **591–592**

- for heat rejection equipment **299–300**
- Drives, multiple-motor 1349**
 - applications. *See* Drives, variable-speed
 - cost 1349
 - efficiency 1349
 - for heat rejection equipment **299–300**
 - retrofitting 1349
 - speed ratios 1349–1350
- Drives, variable-frequency 1350–1370**
 - advantages 1350–1351
 - applications, general. *See* Drives, variable-speed
 - applications, high-torque 1351–1354, 1363
 - how to accommodate 1352–1354
 - motor limitations 1351–1354
 - current source inverter (CSI) drives
 - braking 1369
 - characteristics (table) 1355
 - cogging 1364
 - fault protection 1370
 - harmonic distortion 1360, 1361
 - how they work 1356
 - mechanical vibration 1364
 - multiple motors, limitations 1367
 - noise 1364
 - power factor 1369
 - power system problems 1366
 - regeneration 1369
 - speed increase, limitations 1368
 - turndown ratio 1368
 - waveform 1356
 - cycloconverter 1355
 - ease of installation 1351
 - efficiency 1350–1351, 1367–1368
 - part-load 1367–1368
 - torque, effect on 1368
 - features to consider 1366–1370
 - acceleration control 1367
 - altitude limits 1370
 - braking 1369
 - bypass, emergency 1369
 - control inputs 1366
 - current boost 1367
 - current capacity 1366–1367
 - current limiting 1367–1370
 - diagnostic features 1370
 - displays 1370
 - efficiency 1367–1368
 - fault protection, electrical 1370
 - humidity limits 1370
 - IR compensation 1367
 - multiple motors, ability to drive 1367
 - power factor 1369–1370
 - regeneration 1369
 - restart, automatic 1369
 - reversing capability 1369
 - ride-through 1370
 - soft start 1367
 - speed increase capability 1368
 - speed precision 1368
 - speed range lockout 1368–1369
 - speed settings, fixed 1368
 - start moving motor 1369–1370
 - temperature limits 1370
 - torque characteristics 1351–1352, 1366–1367
 - transients, resistance to tripping 1370
 - turndown ratio 1368
 - voltage boost 1367
 - voltage-speed ratio adjustment 1367
 - how they work 1354–1355
 - load-commutated inverter 1355
 - maintenance 1351
 - motors for
 - cooling limitations 1171–1172, 1352
 - inverter duty 1174, 1363
 - MotorMaster, selecting with 1166, 1174
 - problems 1174
 - ratings for variable-speed use 1352
 - torque requirements 1351–1352
 - power factor 1361
 - prices 1354
 - problems and solutions 1363–1366
 - accelerated meter reading 1366
 - cable length limitations 1365–1366
 - capacitors, power factor correction 1366
 - cogging 1364
 - electrical interference, conducted 1364–1365
 - electrical interference, radiated 1365
 - electrical resonance in motor cable 1366
 - electrical resonance in power wiring 1366
 - fuses blown 1366
 - inefficiency in other equipment 1366
 - mechanical resonances 1364
 - motor efficiency loss 1363
 - motor insulation failure 1363–1364
 - motor overheating 1363
 - motor voltage stress 1361
 - noise, from drive 1364
 - noise, from motor 1364
 - notching 1364
 - overheating other equipment 1366
 - pulse width modulation (PWM) drives
 - braking 1369
 - carrier frequency 1356, 1361
 - characteristics (table) 1355
 - chopper circuit 1356
 - efficiency 1368
 - electrical interference 1361, 1364, 1365
 - fault protection, electrical 1370
 - filter 1356, 1360
 - harmonic distortion 1360, 1361
 - how they work 1356–1357
 - motor cable problems 1365–1366
 - motor failures with 1363–1364
 - motors, driving multiple 1367
 - noise 1361, 1364
 - power factor 1369
 - power system resonance 1366
 - pulse rate 1361
 - regeneration 1369
 - speed increasing capability 1368
 - turndown ratio 1368
 - voltage stress, in motors 1361, 1363–1364
 - waveform 1356, 1363
 - sizes available 1354
 - switching devices 1355
 - bipolar junction transistor 1355
 - commutation 1355
 - Darlington transistor 1355
 - gate turn-off thyristor (GTO) 1355
 - insulated gate bipolar transistor (IGBT) 1355
 - power transistor 1355
 - silicon controlled rectifier (SCR) 1355
 - thyristor 1355
 - turndown ratio 1351
 - types of variable-frequency drives 1355–1356
 - comparison of (table) 1355

variable-voltage input (VVI) drives
 braking 1369
 characteristics (table) 1355
 cogging 1364
 efficiency 1356
 fault protection 1370
 filter 1355, 1360
 harmonic distortion 1360, 1361
 how they work 1355–1356
 mechanical vibration 1364
 motors, driving multiple 1367
 noise 1364
 power factor 1369
 power system problems 1366
 speed increasing capability 1368
 torque 1356
 turndown ratio 1368
 waveform 1355–1356
 voltage-speed ratio 1367
 waveform distortion, caused by
 VFD's
 caused by inverter 1360
 caused by rectifier 1360
 filtering of 1360
 harmonics of inverter frequency, PWM 1361
 harmonics of line frequency 1360–1361
 harmonics of motor frequency 1361
 notching 1360, 1361, 1364
 voltage-current phase shift 1361
 waveform distortion, general
 current 1357–1358
 effect of system impedance 1359
 equipment causing 1357
 harmonic analysis 1358–1359
 how to calculate 1359
 how to measure 1359–1360
 input 1357–1358
 output 1357–1358
 standards for 1360
 voltage 1357–1358

Drives, variable-pulley 1373–1374
 applications. *See* Drives, variable-speed
 cost 1374
 efficiency 1373
 how they work 1373
 maintenance 1374
 physical size 1373
 power capacity 1373
 turndown ratio 1373

Drives, variable-speed 1345–1375. *See also* Drives, direct current (DC); Drives, eddy current clutch; Drives, multiple-motor; Drives, variable-frequency; Drives, variable-pulley; Motors, AC induction: multi-speed; Motors, wound-rotor
 consider overall efficiency 1346
 for air handling systems. *See* Air handling systems, by type
 for centrifugal chillers 335–336
 for centrifugal compressors 1308–1309
 for centrifugal pumps 1340, 1342
 for combustion fans **90–92**
 for heat rejection equipment **291, 295–297**
 for reciprocating compressor 1310
 for VAV systems 627
 not for service water 486
 types of variable-speed drives 1345–1346

Dummy lamps, fluorescent 1050

Dumping (air diffusers) 627

DX. *See* Direct expansion cooling systems

E

Earth sheltered construction. *See* Insulation, types: soil

Earth-coupled heat pumps. *See* Heat pumps: earth-coupled

Economizers, absorption cooling 1327

Economizers, boiler

& air preheaters 126–127

condensing **129–130**

acid condensate, disposing 130

construction 129

cost 130

fuels used with 129–130

where to consider 129–130

conventional (non-condensing)

121–125

acid dew point limitations 122–125

construction 121

energy saving 121

fan and pump energy for 124

fuels used with 122–123, 124

how to protect from acid 123–124

where to consider 121

with multiple boilers 124–125

definition 1291

direct contact. *See* Economizers, boiler: water spray
 install **120**

water spray **131–133**

construction 131

cost 131

environmental benefit 131

equipment 131

recovery temperature limits 131

temperature control

water condition 131

Economizers, cooling system 1305–1306

in screw compressors 1313

Economizers, outside air 547–550

control equipment 549

control sequences 549

ductwork requirements 548–549

energy saving 547–548

effect of internal heat gain 547

effect of system reheat 547

effect of weather profile 547

enthalpy control 549, **551–552**

comfort effects 551

maintenance requirements 551–552

552

where to consider 551

how it works 547

limitations with dual duct systems

548–550

limitations with multizone systems

548–550

limitations with polluted outside air

548

Economizers, waterside. *See* Heat rejection equipment, direct

cooling by: by waterside economizer

Eddy current clutch. *See* Drives, eddy current clutch

EDR (boiler rating) 1295

EER. *See* Efficiency ratings, cooling

Efficacy (lighting). *See also* Lighting,

by type; Lighting, design issues:

lamp characteristics: efficiency

definition 1437

maximum theoretical 1440

table of values 1437–1443

Efficiency codes, laws & standards

ANSI, for ballasts 1060, 1063

ASHRAE Standard 90 1168, 1445

CBM (Certified Ballast Manufacturers) 1063

construction efficiency codes 1445

BOCA 1445

CABO 1445

- for ballasts 1063
 - for lighting **1445**
 - approaches used 1445
 - for motors 1167–1169
 - for water heaters 466
 - lighting equipment standards 1445
 - National Appliance Energy Conservation Act (US)
 - fluorescent ballasts 1445
 - National Energy Policy Act (US)
 - HID lighting 1480
 - lamps 1445
 - National Energy Policy Act (US) 1168
 - NEMA (motors) 1167–1169
 - Efficiency, equipment.** *See* type of equipment
 - Efficiency ratings, cooling 1297–1298**
 - auxiliary equipment, effect of 1298
 - coefficient of performance (COP) 1297
 - energy efficiency ratio (EER) 759, 1297
 - for air conditioners 759
 - where to get 759–760
 - for heat pumps 759
 - where to get 759–760
 - part-load efficiency 1298
 - rating temperatures 1297
 - seasonal energy efficiency ratio (SEER) 759, 1297
 - Efficiency ratings, glazing units 943**
 - Efficiency ratings, heating**
 - for direct-fired units 801
 - for heat pumps 759
 - Heating Seasonal Performance Factor (HSPF) 759
 - Electric boilers.** *See* Boilers: electric
 - Electric vehicles**
 - conflict with thermal storage 411
 - Electrical interference**
 - FCC classes 1365–1366
 - from variable-frequency drives 1365
 - Electricity pricing 1251–1257**
 - commodity charges 1253
 - competitive purchasing 1257
 - customer charge 1257
 - delivery voltage, effect on 1256
 - demand charges
 - & heating storage. *See* Thermal storage, heated water
 - definition 1254–1256
 - load profile, relationship to 1254–1256
 - measurement of 1254
 - peak demand periods 1255
 - reducing, by cooling thermal storage. *See* Thermal storage, cooling
 - reducing, by heating thermal storage. *See* Thermal storage, heating
 - reducing, by water heating control. *See* Water heating: control to reduce demand charges; Water heating: interruptible
 - reducing, by water heating storage. *See* Water heating: storage
 - reducing, with energy management system. *See* Energy management control systems
 - related charges 1254–1255
 - discounts 1256
 - distribution charge 1254–1255
 - equipment ownership, effect of 1256
 - excess-consumption charge 1257
 - for cooling storage 412–413
 - fuel surcharges 1253
 - generation charge 1254–1255
 - hour charges 1255
 - meter charge 1257
 - metering, effects of 1256–1257
 - negotiating rates 1257
 - power factor penalties 1256
 - measurement of 1256
 - ratchet charges 1255
 - rate schedules 1251–1253
 - riders 1252–1253
 - rebates 1256
 - utility's cost components 1251–1253
 - wheeling 1257
- Electrode boiler 1294**
- Electrons**
 - in fluorescent lighting 1459–1464
 - in incandescent lighting 1447–1448, 1463
 - in light emission 1447–1448
- Electrostatic air filters 542**
- Ellipsoidal reflector lamps.** *See* Lighting, incandescent: lamps, reflector
- Emittance**
 - of building surfaces 955–956
 - of glazing. *See* Low-emissivity (low-E) coatings
- Emulsifiers**
 - in fuel oil 179
- Energy analysis computer programs**
 - accuracy of 1242–1244
 - data libraries 1241–1242
 - how to debug 1244–1245
 - how to select 1245
 - how to use 1241–1242
 - output of 1240–1241
 - structure of 1239–1240
 - technical support 1245
- Energy efficiency ratio (EER).** *See* Efficiency ratings, cooling
- Energy levels, of atoms**
 - in fluorescent lighting 1459–1464, 1463
 - in general 1447–1448
 - in incandescent lighting 1447–1448
- Energy management control systems 1219–1226**
 - advantages of 1219
 - capabilities of 1219–1221
 - configurations 1222–1223
 - cost of 1223
 - for complex control functions 1221
 - for controlling many items 1220
 - for creating reports 1219
 - for limiting electrical demand 1221, 1222
 - for monitoring 1219
 - for system control 1220–1221
 - inappropriate uses 1221–1222
 - obsolescence 1226
 - problems with 1223
 - software issues 1225
 - staffing requirements 1224–1225
 - standards for 1226
 - BACnet 1226
 - LonMark 1226
- Energy sources**
 - electricity **1251–1257**
 - fossil fuels **1247–1250**
 - free & renewable **1267–1282**
 - geothermal 1278–1280. *See also* Geothermal systems
 - hydropower 1276–1278. *See also* Hydropower, local
 - photovoltaic 1271–1273. *See also* Photovoltaic systems
 - solar cooling 1268–1271
 - solar heating, active systems 1268–1271. *See also* Solar heating, active
 - solar thermal power systems 1274. *See also* Solar thermal power systems
 - waste product combustion 1280. *See also* Waste product combustion

wind 1274–1276. *See also* Wind energy systems
 wood & biomass combustion 1281. *See also* Biomass combustion; Wood
 free, low-temperature, for heat pumps **1259–1264**
 ground water 1261–1262
 soil 1259–1261
 solar collectors 1263
 surface water 1262–1263
 waste heat 1264
 sunlight **1283–1287**

Enthalpy, outside air
 to control chiller plant **247–248**
 to control economizer cycle. *See* Economizers, outside air

Equinox 1284–1285

Equivalent direct radiation (boiler rating) 1295

Equivalent sphere illumination 1428

Evaporative condensers. *See also* Heat rejection equipment
 definition 1302

Evaporative space coolers 550

Evaporator waterside cleaning **279**
 methods 279
 water treatment for 279

Evaporators, cooling system 1317–1319
 direct expansion (DX) 1318–1319
 evaporators with expansion valves 1317–1318. *See also* Expansion valves, refrigerant
 flooded evaporators 1317
 heat transfer design 1320
 fouling factor 1320–1321
 in absorption machines 1323
 isolate, for idle chillers. *See* Cooling plant, minimize operation: pumps, chilled water
 liquid overfeed evaporators 1317
 series vs. parallel connections 1320–1321
 superheat
 in expansion valves 1318
 reduces system COP 1318–1319
 temperature, maximize. *See* Chilled water temperature, maximize
 turbulators for. *See* Turbulators, for evaporator tubes

Exfiltration. *See* Air leakage, building envelope

Exhaust air
 definition 528
 heat recovery from. *See* Heat recovery, from building exhaust air

Exit signs, install efficient **1041–1042**

Expansion joints, air leakage at 865–866

Expansion valves, refrigerant 1301
 capillary tube 1318
 definition 1317
 electronic 1318
 limit condensing temperature 1318
 superheat 1318

F

F&T traps. *See* Steam traps

Fan-coil units
 3-pipe systems, convert
 to 2-pipe **748–750**
 to 4-pipe **751**
 control
 methods 741
 thermostatic. *See* Heating & cooling units, minimize operation
 to minimize operation. *See* Heating & cooling units, minimize operation
 definition 741
 electric heating, eliminate **752**
 heat trapping against wall, avoid **745–747**
 maintenance **742–743**
 motors, select efficient **744**

Fan-powered VAV terminals. *See* Air handling systems, VAV
 single-duct: terminals, fan-powered

Fans
 air handling system. *See* Air handling systems
 dampers for 1190–1191
 inlet vanes 1190
 exhaust, air for 522
 for burners. *See* Burner systems, fuel
 output, adjusting **1188–1191**
 energy saving 1188
 limitations 1189
 with belt drive 1189–1190
 with inlet vortex damper 1190
 with variable-pitch propeller 1190
 space air circulation 550
 with VAV systems 621

variable-pitch
 for heat rejection equipment **297–298**

Faucet aerators
 efficiency standards for 443
 maintenance **440–441**

Faucets
 efficiency standards for 443
 for showers 446, **448–449**
 maintenance **440**

Feedback (in controls)
 definition 1381

Feedwater, boiler
 definition 137–141

Feedwater systems, boiler. *See* Boiler feedwater systems

Fenestration. *See* Doors; Glazing

Fiberglass insulation. *See* Insulation, types: glass fiber

Film, solar control **944–948**
 & breakage of glazing 945
 & shading devices 944–945
 abrasion resistance 947, 948
 & low-E coatings 946, 947
 adhesive methods 946
 appearance 946, 947
 appearance defects 944
 benefits, non-energy
 breakage protection 945–946
 improved building appearance 946
 color 946, 947
 economics 944
 effect on appearance 944
 effect on daylighting 945, 948
 effect on heat loss 945, 946–947
 effect on passive solar heating 945, 948
 effect on solar heat gain 945
 effect on view 947
 energy penalties 945
 energy saving 945
 how it works 946–947
 how to clean 948
 how to install 947–948
 how to select 947
 limitations 944–945
 low-E features 945, 946–947
 & abrasion resistance 946
 materials 946
 on treated glazing 945
 optical properties 946
 reflection vs. absorption 946, 947
 service life 944
 ultraviolet absorption 946

Filters, air

- adsorbent 541
- chemical 541–542
- electrostatic 542
- HEPA 540–541
- to reduce ventilation
 - requirements. *See* Ventilation,
 - outside air: reduce, by air cleaning
- ultraviolet 542–544

Firetube boilers. *See* Boilers: firetube

Fixtures, service water

- install efficient
 - shower heads. *See* Shower heads: install efficient
 - toilets. *See* Toilets: install efficient
 - urinals. *See* Urinals: install efficient
- wash basins. *See* Wash basins: efficient fixtures, install
- maintenance **440–442**
 - basin stoppers 441
 - faucet aerators 440–441
 - faucets 440
 - flushometer valves 441
 - shower heads 441–442
 - toilets 441
 - valves 440

Flame spread, of insulation materials

1396

Flash intercooling 1305–1306

Float traps. *See* Steam traps

Float valve, refrigerant 1301

Flow measurement

- equipment quality 1236
- flowmeters 1233–1236
 - calibration of 1237
 - display features 1237–1238
 - orifice 1235
 - pitot tube 1234–1235
 - propeller 1233–1234
 - rotameter 1235–1236
 - spring-loaded variable-area 1236–1238
 - turbine 1233–1234
 - ultrasonic 1234
 - variable-area 1235–1236
 - venturi 1235
 - vortex shedding 1234
- for gases and vapors **1233–1238**
- for liquids **1233–1238**
- system components 1233
- totalizers 1236

Flow restrictors, shower head 447

Flowmeters 1233–1236

Flue dampers, automatic

- energy saving 104
- for boilers **104–105**
 - where to consider 104
 - where to install 105
- for direct-fired heaters **802–803**
 - energy saving 802
 - where to consider 802
- for water heaters **469**
 - installation difficulty 469
 - where to consider 469
- how to install 803
- okay with pilot lights 105
- safety certification 105, 803
- types of flue dampers 105, 802
 - externally powered 105, 802
 - self-powered 105, 802

Flue draft. *See* Draft, combustion

Flue gas

- acid dew point
 - definition 122–123
 - limits heat recovery 121, 122–123
 - values for typical fuels 123
- heat recovery from. *See* Air preheaters, boiler; Economizers, boiler
- recirculation, in burner systems 79
- scrubbers, cost of 1250
- temperature
 - & boiler efficiency. *See* Boiler efficiency testing
 - & economizers. *See* Economizers, boiler
 - factors that determine 120

Fluidized bed boilers. *See* Boilers:

fluidized bed

Flush valves

maintenance **441**

Foam insulation. *See* Insulation,

types: plastic foam

Foaming, in boilers. *See* Water

treatment, boiler water

Footcandle. *See also* Lighting, design

issues; Lighting, measurements

definition 1423

Forgiveness clause, for cooling

storage rates 413

Fossil fuels 1247–1250

- acid dew point of 1249
- and flue gas temperature 1249
- availability 1250
- coal 1248–1249
- combustion products 1248
- composition of 1247–1248
- contaminants 1248

- cost factors 1249–1250
- efficiency-related characteristics 1247–1249
- energy content of 1248–1249
 - high heat value 1248–1249
 - low heat value 1248–1249
- excess air requirements 1249
- fuel oil 1248–1249
- hydrogen content, effects of 1249
- natural gas 1247–1249
- storage and handling 80, 1250

Fouling factor

- definition 1320
- in condensers 1320–1321
- in evaporators 1320–1321

Frederick the Great 1276

Free cooling. *See* Heat rejection

equipment, direct cooling by

Free energy sources. *See* Non-fossil

energy sources

Freeze protection

- for steam coils 568–569
- in air handling systems. *See* Air handling systems: freeze protection
- in hydronic systems 568

Fuel oil. *See also* Fossil fuels

additives **178–180**

alternatives to 180

be skeptical about 179–180

to catalyze combustion 178

to improve atomization 178

to prevent fuel system corrosion

179

to prevent stratification 179

to reduce fireside fouling 178

to reduce sludge 179

fuel properties of 1247–1249

heating

use most economical source **177**

with waste heat 177

temperature. *See* Fuel oil: viscosity

viscosity

automatic control to optimize **176**

efficiency, effect on 174

how to measure 175

optimize **174–175**

units of 175

variation of 174–175, 175

Fuel oil systems

functions 173

motors, high-efficiency **180**

Fuel selection, boilers 28–29, 30

automatic **30**

how to install 30

how to calculate 28

Fuel surcharges, in electricity rates

1253

Fuel value, of insulation materials

1396

Fuel-air ratio. *See* Air-fuel ratio**Fuels.** *See* Fossil fuels**Furnaces, forced-air.** *See* Direct-fired heating units**G****Gate turn-off thyristor (GTO)** 1355**Geothermal heat pumps.** *See* Heat pumps: earth-coupled**Geothermal systems** 1278–1280. *See**also* Heat pumps: earth-coupled

applications 1279

depths of wells 1279

development status 1279

economics 1279

environmental issues 1279

extraction techniques 1279

geothermal sources 1278–1279

life of source 1278

temperatures available 1278

Glare. *See* Daylighting, design

issues; Lighting, design

issues; Lighting, fixture layout

definition 1430

Glass. *See also* Glazing

absorption, far infrared 937

Glass fiber insulation. *See* Insulation, types: glass fiber**Glazing**

appearance 942–943

area, reducing. *See* Shading, to

reduce cooling load: by reducing glazing area

breakage

& solar control films 945

protection by films 945–946

thermal 945

color 942

efficiency features

absorption 939–940

frames, insulating properties 936–937

gap between panes 939

insulating fill gases 938

integral shading devices 940

low-E coatings 937–938

number of surfaces 936

reflection 939–940, 942

seal reliability 939

efficiency ratings 943

energy consumption effects 934

frames 936–937

avoid leakage around 941

thermal breaks 936–937

install efficient **934–943**

for daylighting 941

for minimum air leakage

940, 941

for minimum heat gain 939–940

for minimum heat loss 936–939

for passive solar heating 940–941

how to plan 935–936

where to retrofit 934

install supplemental **908–910**

condensation, preventing 909

energy saving 908–909

exterior glazing 909

how to install 910

interior glazing 909

ventilation, providing 909–910

vs. total window replacement 910

longevity 941–942

maintenance **860**

privacy 943

shading for. *See* Shading, to reduce cooling loadstorm windows. *See* Glazing: install supplemental

thermal breakage, avoiding 941

view through 942

Global warming, & refrigerants

1336–1338

Greenhouse effect, in global warming

1336–1338

Greenhouse gases 1336–1338**Greenhouses.** *See* Daylighting, by translucent roof & walls; Solar heating, passive: by glazed enclosures**Ground source heat pumps.** *See* Heat pumps: earth-coupled**Ground water**as heat sink and heat source. *See*

Heat pumps: ground water source

Group relamping. *See* Lighting, maintenance**H****Halocarbon refrigerants.** *See* Refrigerants**Halogen cycle (lamps)** 1451–1452**Halogen lamps.** *See* Lighting, incandescent: lamps, tungsten halogen**Hardness, water.** *See also* Water treatment, boiler water definition 145**Harmonic distortion.** *See* Waveform distortion, electrical power**Hatches, roof.** *See* Roof hatches**HCFC refrigerants.** *See* Refrigerants**Heat**

radiation 1229

Heat exchanger. *See also* Heat recoveryair-to-air **555–562**

evaporative cooling of 560–561

flue gas. *See* Air preheaters,

boiler; Economizers, boiler

heat pipe 556–557

heat wheel, latent 558–559

heat wheel, sensible 557–558

permeable medium 556

plate, for air 556

runaround loop 559

Heat, in general

definition 1387

how heat moves

conduction 1387–1388

convection 1388

mass transfer 1388

radiation 1388

infrared radiation 1387

latent heat. *See* Latent heat**Heat loss.** *See also* Heat, in general:

how heat moves

from buildings. *See also* Infrared thermal scanning

from hot surfaces 212

from wet insulation 212–213

Heat meters 1236

for boiler plants 55

Heat pipe. *See* Heat exchanger**Heat pump loop systems**

advantages 780–781

cost 782

description 779–780

efficiency penalties 781

efficiency pitfalls 788–789

flaws, common 783

heat sinks **791–793**heat sources 780–784, 786–788, **791–793**loop isolation valves **789–790**optimize loop temperature **785–789**

with thermal storage 788

separate high-/low-temperature headers 783–784

solar collectors for 781–784

cost advantage 792

space-to-space heat recovery 780–784, 782

temperature limits 786

- thermal storage for 781, **794–795**
 - energy & cost saving 794–795
 - where to consider 794
- Heat pumps**
 - air leakage around, prevent **757**
 - compressors, install efficient **767**
 - earth-coupled **1259–1261**
 - advantages of 1260–1261
 - disadvantages of 1261
 - types of soil heat exchangers 1259–1260
 - efficiency ratings. *See* Efficiency ratings, cooling; Efficiency ratings, heating
 - fan motors, install efficient **756**
 - for heat recovery **394–397**
 - geothermal. *See* Heat pumps: earth-coupled
 - ground water source **1261–1262**
 - advantages of 1261–1262
 - disadvantages of 1262
 - heat sinks for **1259–1264**
 - heat sinks, install alternative. *See* Heat pumps: heat sources, install alternative
 - heat sources for **1259–1264**
 - heat sources, install alternative **775–778**
 - design issues 777
 - options in new construction 775–776
 - options in retrofit 776–777
 - where to consider 775
 - install efficient **759–760, 767**
 - cost, relative 760
 - efficiency ratings 759
 - other features 760
 - size, relative 760
 - loop systems. *See* Heat pump loop systems
 - maintenance
 - for self-contained units **754–756**
 - for split systems **765–766**
 - motors, install efficient **766**
 - solar collectors as heat source **1263–1264**
 - advantages of 1263
 - disadvantages of 1263–1264
 - sump heaters, seasonal operation **770**
 - surface water source **1262**
 - advantages of 1262
 - disadvantages of 1263
 - ventilation, eliminate inefficient **758**
 - waste heat as heat source **1264**
 - well water source. *See* Heat pumps: ground water source
- Heat recovery, from blowdown** 140–141, **158–162**
 - for heating feedwater 161
 - for heating makeup water 160
 - from blowdown water only 158
 - from flash steam 158
 - heat available 158–159
 - heat exchanger for 162
 - safety issues 162
 - with condensate heat recovery 161–162
- Heat recovery, from boiler room air** **218–223**
 - comfort 223
 - energy saving 218
 - how to do 219–223
 - safety 223
- Heat recovery, from building exhaust air** **555–562**
 - application restrictions 560
 - between multiple air streams 561
 - contamination between air streams 561
 - control 561
 - economizer cycle, with 562
 - efficiency 559–560
 - energy saving 560
 - fan energy requirement 559
 - fire hazard 561
 - freeze protection 561
 - heat exchanger
 - evaporative cooling of 560–561
 - heat pipe 556–557
 - heat wheel, latent 558–559
 - heat wheel, sensible 557–558
 - how to select 561
 - permeable medium 556
 - plate 556
 - runaround loop 559
 - types of heat exchangers 556–559
 - heat exchanger cleaning 561
 - heat recovery, latent 555, 559
 - heat recovery, sensible 555, 559
 - installation problems 561
 - pump energy requirement 559
- Heat recovery, from condensate.** *See also* Condensate systems: maximize condensate return
 - from discarded condensate **166**
 - from high-temperature condensate **167–168**
 - energy in flash steam 168
- Heat recovery, from cooling equipment**
 - adjusting load, recovery vs. non-recovery 388
 - amount of heat available 385
 - by auxiliary or double-bundle condenser **391–393**
 - contamination by refrigerant 392
 - control 392–393
 - energy saving 392
 - leakage into refrigerant 392
 - recovery temperature 391
 - sizing 391
 - by desuperheater **397–399**
 - contaminant isolation 399
 - equipment 398–399
 - from ammonia 387
 - heat recovery potential 397–398
 - limitations 398
 - refrigerants with high superheat 398
 - where to consider 397–398
 - by direct use of condenser cooling water **389–390**
 - controls 390
 - energy saving 389
 - isolation from contaminants 389
 - by heat recovery chiller **394–397**
 - cost 395
 - energy recovery potential, net 394–395
 - how to distribute cooling load 395
 - operation at low condensing temperature 395, 403
 - selecting type of compressor 395–396
 - sizing 395
 - use of chiller for cooling storage 396
 - condensing temperature, increasing 385–386
 - effect on cooling capacity 386
 - effect on COP 386
 - effect on equipment life 386
 - limitations of centrifugal compressors 386
 - from absorption chillers 387
 - from air conditioners **773–774**
 - from ammonia superheat 387
 - from lead chiller 359
 - from screw compressor oil heat 386–387
 - from split systems **773–774**
 - heat exchange losses 387–388
 - isolation from contaminants 387–388
 - matching application temperature 387
 - matching application timing 387

Heat recovery, from flue gas. *See* Air preheaters, boiler; Economizers, boiler

Heat recovery, from lighting 625–626, 626

Heat recovery, from steam vents 208–209

how to find leaks 208–209
methods 208

Heat recovery, in feedwater systems 140–141

Heat recovery, to heat fuel oil 177

Heat rejection equipment, direct cooling by

alternatives to 370

by chiller "free cooling" 371–373

advantages 372

disadvantages 372

how to control 372

where to consider 371–372

by heat exchanger in CHW system 373–375

advantages 373

disadvantages 373

how to control 374–375

installation 373–374

where to consider 373

by heat rejection unit in CHW system 382–383

freeze protection 383

how to control 382–383

type of cooler 382

where to consider 382

by strainer cycle 375–378

cleaning tower water 376

efficiency of 375

expansion tanks, adapting 377

flow rates, matching 377

how to control 377

system fouling hazard 375

water treatment 376–377

where to consider 375–376

by waterside economizer 379–381

efficiency 379–380

how to control 381

installation 380–381

where to consider 379

comparison of methods 369

where to consider 367–369

Heat rejection equipment, efficient installation

adjust water distribution 307

air recirculation, avoid 310

energy waste from 310–311

factors that cause 311–312

how to minimize 312–314

motors, install high-efficiency 315

secure access panels 309

to minimize debris 305–306

elevate units 305–306

install screens 305

Heat rejection equipment, efficient modulation

by dual/multi-speed fan motors

291–294, 299–300

control issues 299

cost 294

efficiency 292–293, 299

fan size range 293

gearbox lubrication 293

how to select 299

in multi-fan equipment 300

maintenance 294

noise reduction 294

resonances 293

retrofit, ease of 294

starting stress 294

by efficient fan sequencing 301–302

how it lowers condenser temperature 301

how it saves energy 301

by multi-speed fan motors

resonances 300

by variable-pitch fans 291–

294, 297–298

control issues 298

cost 294

drive, belt vs. gear 298

efficiency 292–293

fan size range 293

maintenance 294

noise reduction 294

resonances 293, 297–298

retrofit, difficulty of 294

starting stress 294

turndown ratio 297

by variable-speed fan drives 291–

294, 295–297

control issues 295–296

cost 294

efficiency 292–293

electrical interference 293, 295

fan size range 293

for multiple fans 293

gearbox lubrication 293

maintenance 294

motors, whether to replace 296

noise reduction 294

resonances 293, 295

starting stress 294

turndown ratio 295

by variable-speed fans

retrofit, ease of 294

comparison of methods 292–294

condensing temperature, effect on

292

cooling efficiency, effect on 294

energy saving 291–292

other benefits 292

Heat rejection equipment, health hazards 564–565

Heat rejection equipment, maintenance

cleaning 302–304

energy saving 302

how to clean dry coolers 303

how to clean wet coolers 303–304

fouling, causes 302

keep air flow intact 308–309

seasonal shutdown 770–771

Heat rejection equipment, minimize operation 250–252, 772–773

energy saving 250–251, 772

how to control 251–252, 772

pumps, spare 260

where to consider 250–251, 772

Heat sinks, for heat pumps and cooling equipment 1259–1264

install alternative. *See* Air conditioners: heat sinks, install alternative

Heat sources

for heat pump loop systems 786–

788

for heat pumps 1259–1264

fossil fuels. *See* Fossil fuels

free & renewable. *See* Non-fossil

energy sources

free, for heat pumps

installation. *See* Heat pumps

Heat wheel. *See* Heat exchanger

Heaters

for cooling towers

seasonal shutdown 770–771

Heaters, sump. *See* Sump heaters, compressor

Heating & cooling units, minimize operation

by clock control 711–713

applications 711

energy saving 712

how to install 712–713

how to select 712

override 712

by door & window switches 716

energy saving 716

how to install 716

placards for 716

by light switch **714**
 applications 714–715
 how to connect 715
 by personnel sensor **714**
 by placards **704–707**
 applications 704
 energy saving 704–705
 placard design 705
 where to install 706
 by setback thermostat **711–713**
 applications 711
 energy saving 712
 how to install 712–713
 how to select 712
 override 712
 setback temperature 711–712

Heating equipment
 absorption chillers 1328–1329
 boilers. *See* Boiler plant; Boilers
 direct-fired heating units. *See*
 Direct-fired heating units
 fan-coil units. *See* Fan-coil units
 furnaces, forced-air. *See* Direct-fired
 heating units
 heat pump loop systems. *See* Heat
 pump loop systems
 heaters, direct-fired. *See* Direct-fired
 heating units
 minimize operation. *See* Heating &
 cooling units, minimize operation
 radiators. *See* Radiators

**Heating Seasonal Performance
 Factor (HSPF).** *See* Efficiency
 ratings, heating

Heating, solar. *See* Solar heating,
 active; Solar heating, passive

Heating storage. *See* Thermal storage,
 heated water

Heating surface (boiler rating) 1295

Helical rotary compressors. *See*
 Compressors, cooling, screw

HEPA filters 540–541

Hermetic compressors
 definition 1315

HFC refrigerants. *See* Refrigerants

High-frequency ballasts. *See* Light-
 ing, fluorescent; Lighting, high
 intensity discharge

Hoods
 draft hoods. *See also* Draft, combus-
 tion: draft regulators
 ventilation air for
 how to reduce 522

**Horsepower (boiler rating), defini-
 tion** 1294–1295

Hot gas bypass
 in centrifugal compressors 1308

Hot water temperature 458–460
 & recirculation 460
 energy use, effect on 458
 hazard, infection 458–459
 & type of water heater 459
 hazard, scalding 459, 475
 how to select 459–460
 in storage heating systems 475
 low-temperature detergents, to
 reduce **461**
 storage capacity, effect on 460, 475
 thermometers for 460

Hour charges, for electricity 1255

House wraps 1393–1394

HSPF. *See* Efficiency ratings, heating

Hydrazine, for water treatment 146

Hydronic cooling systems
 definition 1302

Hydronic heating systems
 advantages 734
 convert steam to **733–735**

Hydropower, local 1276–1278
 applications 1277
 connection to public utilities 1278
 development status 1277
 economics 1278
 energy availability 1277–1278
 environmental issues 1278
 high-head and low-head 1277
 PURPA, effect of 1278
 system components 1277
 terrain preparation 1277

Hypersensitivity pneumonitis 565

Hysteresis, in controls 1379

I

IBR ratings (for boilers) 1295

Identification. *See* Placards

**IEEE Standard 519 (waveform
 distortion)** 1360

Ignitors. *See* Lighting, high intensity
 discharge

Illuminance. *See also* Lighting, design
 issues: illumination level
 definition 1423

Impedance
 of power systems 1359
 of transformers 1359

Impeller, pump. *See* Pumps, centrifugal

Impeller trimming, pump. *See*
 Pumps, centrifugal: impeller
 trimming

Induction loop sensors 852

Infiltration. *See* Air leakage, building
 envelope

Infrared radiation. *See also* Infrared
 thermal scanning
 definition 1387
 from incandescent lighting 1450
 in sunlight **1283–1284**
 & emittance of opaque surfaces
 955–956
 & solar control films. *See* Film,
 solar control
 absorption by opaque surfaces
 955–956
 amount 955–956
 selective absorption by glazing
 934, 939
 intensity vs. source temperature
 1229
 long-wavelength
 & low-E coatings. *See* Low-
 emissivity coatings
 absorbed by glass 937
 heat gain 935
 heat loss from buildings 935
 origin 1229
 wavelength vs. source temperature
 1229

Infrared switches. *See* Personnel
 sensors: infrared

**Infrared thermal scanning 1229–
 1232**
 capabilities 1229
 estimating air leakage heat loss
 1232, 1384
 estimating conductive heat loss
 1231–1232
 for heating plant insulation 214
 for steam trap testing 201
 limitations 1229
 survey conditions 1231
 types of scanners 1230
 where to get equipment 1232

Inlet guide vanes
 for centrifugal compressors 1308
 for fans. *See* Fans: dampers for:
 inlet vanes

**Insulated gate bipolar transistor
 (IGBT)** 1355

Insulation, economics 1396–1399

Insulation, for attics 876–878
 appropriate types 876–877
 blankets & batts, installing 877
 loose fill, installing 877
 protecting 877
 vapor barrier for 877
 venting moisture from attic 877

Insulation, for condensate pipe 164

Insulation, for doors. *See* Doors, by
 type

Insulation, for heating plant equipment 212–216

- condensate system 214
- heat loss from bare surfaces 212
- heat loss from wet insulation 212–213
- how to find defective 214
- in pipe tunnels 213, **216–217**
- installation 215
- materials 214–215
- what not to insulate 213–214
- what to insulate 213–214

Insulation, for hot service water pipe 493

- effect on pump power 493

Insulation, for roofs

- exterior rigid insulation **879–882**
 - advantages 879
 - drainage 881
 - types of roof insulation 880
- exterior sprayed foam **882–883**
 - advantages 882
 - disadvantages 882–883
 - drainage 883
 - protection 883
- for interior surface **884–885**
 - advantages 884
 - attachment 885
 - moisture damage, how to avoid 884–885
 - moisture damage, risk of 884
 - to reduce solar heat gain **954**

Insulation, for suspended ceiling 886–887

- applications, cooling 886
- applications, heating 886–887
- reducing space volume 887

Insulation, for walls

- for curtain walls **903–905**
 - air leakage, avoiding 905
 - materials 905
 - panel design 905
 - retrofit feasibility 904–905
 - with other improvements 905
- for exterior surface **901–902**
 - advantages 901
 - convection loss, avoiding 901–902
 - moisture problems, avoiding 902
 - protection for 902
 - types of exterior insulation 901
- for interior surface **896–900**
 - air leakage, avoiding 899
 - materials 896
 - moisture damage, avoiding 896

- with impermeable walls 899
- with permeable walls 896–899
- for wall cavities **890–895**
 - energy saving 890
 - fire safety 895
 - retrofit, in masonry walls 893–895
 - retrofit, in stud walls 890–893
 - vapor barriers 895
- to reduce solar heat gain **954**

Insulation, for water heaters 465–466, 475**Insulation, for windows**

- high-efficiency glazing. *See* Glazing: install efficient
- low-E coatings 937–938
- low-E retrofit films **912, 944–948**
- storm windows. *See* Glazing: install supplemental
- supplemental glazing. *See* Glazing: install supplemental
- thermal shutters **911–912**
 - security benefit 911
 - vs. storm windows 911

Insulation, how it works 1387–1390

- fiber insulation 1387–1388
- foam insulation 1388
- gases in insulation 1388
- granular insulation 1387–1388
- mass effects 1389
- preventing conduction 1387–1388
- preventing convection 1388–1390
- preventing heat radiation 1388
- preventing mass transfer 1388
- reflective insulation 1389–1390
- time lag in conduction 1389

Insulation, how to install 1401–1402

- avoiding conduction paths 1401
- avoiding convection 1402
 - batt insulation 1402
 - loose fill insulation 1402
 - rigid insulation 1402
- avoiding moisture damage 1389
- vapor barriers **1391–1394**
- venting 1402
- water drainage 1402

Insulation, movable. *See* Movable insulation**Insulation, selection issues 1395–**

- 1399. *See also* Insulation, types**
- aging characteristics 1397
- care required in installation 1396
- cost 1396
- density 1388
- ease of installation 1396
- emissions 1397
- fire characteristics 1396

- microorganism growth 1397
- moisture resistance 1389, 1397
- orientation 1389
- permeability 1397
- physical damage, resistance to 1397
- R-value 1395
- settling tendency 1396–1397
- temperature 1389
- temperature range 1397
- vermin resistance 1397
- void filling 1396

Insulation, types 1397–1399. *See also* Insulation, selection issues

- cellulose, loose dry 1399
 - composition 1399
 - fire characteristics 1399
 - installation 1399
 - moisture degradation 1399
 - R-value 1395
 - settling tendency 1397, 1399
 - vermin 1399
- cellulose, wet sprayed 1399
 - application 1399
- fiber, generally 1387
- foam, generally 1388
- glass fiber 1388, 1397–1398
 - batts 1397–1398
 - blankets 1397–1398
 - boards 1397–1398
 - care required in installation 1396
 - density & R-value 1398
 - fire characteristics 1396
 - health hazards 1398
 - loose fill 1397–1398
 - R-value 1395, 1397
 - vapor barrier, attached 1398
 - vapor barriers for 1392
- glass foam 1388
- granular, generally 1387
- lightweight concrete 1399
 - composition 1399
 - R-value 1395
- mineral fiber 1398
 - R-value 1395
- perlite 1399
 - composition & manufacture 1399
 - in lightweight concrete 1399
 - R-value 1395
- plastic foam, beads 1398
 - fire characteristics 1398
 - in lightweight concrete 1398
- plastic foam, boards 1398
 - aging 1398
 - ease of handling 1398
 - permeability 1398
 - polyisocyanurate, extruded 1398

polystyrene beadboard 1398
 polystyrene, extruded 1398
 polyurethane, extruded 1398
 R-value 1395, 1398
 temperature ranges 1398
 vapor barrier, as its own 1393
 plastic foam, generally
 fire characteristics 1396, 1398
 impact resistance 1397
 permeability 1397
 R-value degradation 1397
 sunlight degradation 1397
 plastic foam, sprayed 1399
 application 1399
 impact protection 1399
 puddling 1399
 sunlight protection 1399
 reflective 1389–1390
 for hot surfaces 215
 soil 1399
 cost of use 1399
 problems 1399
 urea formaldehyde
 chemical emissions 1397
 vermiculite 1388, 1399
 composition & manufacture 1399
 fire characteristics 1399
 handling 1399
 in lightweight concrete 1399
 R-value 1395, 1399

Inverted bucket traps. *See* Steam traps

Inverter drives. *See* Drives, variable-frequency

Ion exchange (water treatment) 145–146

Ionization

 definition 1460
 in fluorescent lighting 1460, 1463

Isocyanurate insulation 1398

J

Jackshaft (boilers) 63

K

Kelvin temperature (lamps) 1442–1443

Kinematic viscosity 175

Krypton

 in fluorescent lamps 1463
 in incandescent lamps 1025, 1451

L

Latent heat

 definition 1299, 1332
 in building air
 recovery by exhaust air heat
 recovery system **555–562**
 in flue gas
 recovery in condensing boilers 1294
 recovery in condensing economizer **129**
 recovery in condensing furnaces 800
 recovery in direct-contact heat recovery unit **131–133**
 recovery in high-efficiency water heaters **463–467**
 in heat pipes 556–557
 in steam
 recovery from boiler blowdown **158–162**
 recovery from discarded condensate **166**
 recovery from high-temperature condensate **167–168**
 recovery from steam vents **208–209**
 of refrigerants 1332

Latent heat wheels 558–559

Leakage, refrigerant. *See* Cooling system leakage

Legionnaires' Disease 565

Light

 how it originates **1447–1448**

Light beam switches 1206–1207

Light meters 1423

Light pipes. *See* Daylighting, by light pipes

Light shelves. *See* Daylighting, by light shelves

Lighting, arc 1449, 1450, 1451

Lighting, control of

 by assigning staff for **1090**
 by door switches **1113**
 by key switches **1095**
 by personnel sensors **1109–1110**
 overrides, avoid 1109–1110
 survey & planning 1109
 types of personnel sensors 1109
 where to use 1109
 by photocontrol, for exterior **1101–1103**
 current capacity 1102
 durability 1101
 how to install 1102

 how to select 1101–1102
 mounting methods 1101
 response delay 1101–1102
 sensitivity settings 1101
 with other controls 1102
 by photocontrol, for interior **1104–1108**
 circuit layout 1107
 HID limitations 1105
 mounting methods 1106
 number of sensors 1106
 sensitivity settings 1106–1107
 where to consider 1104–1105
 with other controls 1105
 by programmable controller **1144**
 to avoid duplication 1140
 user instructions 1144
 by pullcord switches **1147–1149**
 how to install 1147–1149
 where to use 1147
 by relays 1143
 by timeclock **1098–1099**
 astronomical timeclocks **1100–1101**
 how to select 1099
 where to consider 1098–1099
 by timed-turnoff switches **1111–1112**
 overrides, avoid 1111
 safety limitations 1111–1112
 types of timer switches 1111
 circuits. *See* Lighting, fixture layout
 convenience **1145–1146**
 at activity areas 1145–1146
 at exits 1145
 for transit 1146
 distinguish special switches
 by contrasting switch color **1094**
 by decal **1094**
 by lighted toggle **1094**
 by separate mounting 1091, **1094**
 by telltale lights **1093**
 for task lighting 1129
 from multiple locations 1143
 placards for. *See* Placards: for lighting controls
 to avoid duplicated lighting 1140
 with programmable controller 1140
 with transfer switch 1140
 toggle switches, install properly **1091**
 when substituting single-tube ballasts 1051

- Lighting, design issues 1425–1435.** *See also* Daylighting, design issues; Lighting, layout
- area lighting 1428–1429
 - background lighting **1429–1430**
 - & energy efficiency 1430
 - & visual comfort 1429–1430
 - & visual efficiency 1429
 - island of light 1430
 - partitions 1430
 - surface colors 1430
 - brightness
 - & glare 1424
 - & visual comfort 1425
 - & visual efficiency 1425
 - definition 1424
 - of background 1429–1430
 - of task area 1428
 - of various objects (table) 1430
 - color rendering **1434–1435**
 - & color vision defects 1435
 - & illumination level 1435
 - how humans see color 1434, 1435
 - how lamps reveal color 1434
 - loss, in dim light 1435
 - of lamps 1435. *See also* Lighting, fluorescent; Lighting, high intensity discharge; Lighting, incandescent
 - of sunlight 1434–1435
 - design approach, overall 1018–1019
 - design methods, conventional 1019–1020
 - economics, overall 1018
 - efficiency. *See* specific topic
 - efficiency standards. *See* Efficiency codes, laws & standards
 - energy saving potential, overall 1017–1018
 - esthetics 1429–1430
 - glare
 - & age of viewer 1431
 - & background lighting 1429
 - & brightness 1430–1431
 - & visual comfort 1430
 - duration of exposure 1430
 - from light sources 1083, 1119, **1430–1431**
 - from reflections of light source 1122–1123, 1433
 - from veiling reflections 1431. *See also* Lighting, design issues: veiling reflections
 - position of light source 1430
 - size of light source 1430
 - heat recovery. *See* Heat recovery, from lighting
 - illumination level **1425–1427**
 - & color rendering 1435
 - & visual comfort 1427
 - & visual efficiency 1426–1427
 - age of viewer 1426
 - contrast in task 1426
 - office work 1427
 - recommendations 1426
 - size of details 1426
 - illumination, uniformity of **1427–1428**
 - in task lighting 1119–1121
 - lamp characteristics **1437–1443.** *See also* Lighting, fluorescent; Lighting, high intensity discharge; Lighting, incandescent; Lighting, low-pressure sodium
 - ability to substitute lamps 1440–1443
 - ballast energy requirement 1440–1443
 - color, lamp 1441–1443
 - color rendering index (CRI) 1441–1443
 - decorative options 1443
 - dimming ability 1440–1443
 - efficiency 1437–1443
 - electrical interference 1443
 - harmonic distortion 1443
 - lamp & ballast noise 1443
 - light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen output 1437–1443
 - mismatch potential 1440–1443
 - mounting position limitations 1443
 - power factor 1443
 - service life 1437–1443
 - temperature, effect on output 1442–1443
 - temperature, starting 1442–1443
 - time to restart 1442–1443
 - time to start 1442–1443
 - layout. *See* Lighting, fixture layout
 - light intensity, measuring **1423–1424**
 - luminance. *See herein* brightness photography 1441
 - shadowing, by the viewer **1429**
 - in task lighting 1121
 - shadowing, within the task **1428–1429**
 - harsh lighting 1428
 - in task lighting 1122
 - surface area of fixtures 1428–1429
 - task lighting. *See* Task lighting
 - veiling reflections **1431–1434**
 - & reflected glare 1433
 - conditions that cause 1432
 - definition 1431
 - discomfort from 1431
 - energy waste 1431–1432
 - how to avoid 1433
 - in task lighting 1119
 - polarization of light 1433–1434
 - smoothness of surface 1432–1433
 - strength of 1432–1433
 - visual comfort 1425
 - & background lighting 1429–1430
 - & glare 1430
 - & illumination level 1427
 - eye strain 1427
 - in task lighting 1121
 - measuring 1425
 - visual comfort probability 1425
 - visual efficiency **1425**
 - & background lighting 1429
 - & illumination level 1425, 1426–1427
 - age of viewer 1426–1427
 - contrast within task 1425, 1426
 - desensitization by glare 1429
 - in task lighting 1121
 - size of task details 1425, 1426
 - visual quality **1425–1435**
- Lighting efficiency improvements, fluorescent.** *See also* Lighting, fluorescent
- ballasts, disconnect unused **1053**
 - ballasts, substitute lower wattage **1057–1063**
 - ballasts, lamps or both? 1057–1058
 - retrofit applications 1058
 - selection factors 1060–1063
 - types of ballasts 1058–1060
 - current limiters, install **1064–1065**
 - compatibility 1064–1065
 - how to install 1064–1065
 - where to consider 1064
 - lamps & ballasts, remove excess **1046–1049**
 - ballast connection limitations 1046–1047
 - benefits 1046

- disadvantages 1046
- fixture labeling 1049
- how to disable ballasts 1049
- how to remove lamps 1048–1049
- illumination levels 1047–1048
- outer or inner tubes? 1048
- planning 1047–1048
- public relations 1048
- rewire ballasts between fixtures **1052**
- socket adapters 1048, 1070
- substitute single-tube ballasts **1051**
- visual quality 1048
- where to delamp 1046
- with dummy lamps. *See* Dummy lamps, fluorescent
- lamps, substitute dummy lamps **1050**
 - how to install 1050
 - problems 1050
- lamps, substitute lower wattage
 - fixture labeling 1056
 - selection factors 1054–1056
 - where to consider 1054
- reflector retrofits **1069–1070**
 - energy saving, actual 1069–1070
 - for downlights **1038**
 - how they don't work 1069
 - materials 1070
 - socket adapters for 1070
- Lighting efficiency improvements, HID.** *See also* Lighting, HID
 - ballasts, selection factors 1075–1076
 - combine with other types 1139
 - fixtures, upgrade 1074
 - lamps & ballasts, install efficient **1073–1077**
 - energy saving 1073
 - where to upgrade 1073–1074
 - lamps, mercury vapor, direct replacement for **1078–1079**
 - energy saving 1078
 - fixture labeling 1078–1079
 - how to select 1078
 - where to consider 1078
 - lamps, selection factors 1074–1075
 - lamps, substituting smaller 1074
 - substitute fluorescent **1081–1084**
 - relative efficiency 1082–1083
 - selection factors 1083
 - where to consider 1081
- Lighting efficiency improvements, incandescent.** *See also* Lighting, incandescent
 - dimmers, install **1042–1043**
 - efficiency limitations 1042
 - electrical interference 1043
 - placards for 1043
 - types of dimmers 1042–1043
 - exit signs, replace with fluorescent or LED **1041–1042**
 - fixtures, improve shades **1036–1037**
 - fixtures, install flexible extensions in **1039**
 - fixtures, install reflective inserts **1038**
 - fixtures, replace with fluorescent or HID **1040**
 - lamps, reduce wattage **1023–1024**
 - fixture labeling 1023
 - lumen degradation, account for 1023
 - planning 1023
 - with dimmers 1024
 - lamps, substitute compact fluorescent **1025–1030**
 - energy saving 1025, 1026
 - fixture labeling 1030
 - limitations 1026
 - selection factors 1026–1030
 - service life 1025
 - lamps, substitute to minimize light loss **1033–1035**
 - fixture labeling 1035
 - lamp options 1033–1034
 - selection factors 1034–1035
 - lamps, substitute tungsten halogen **1031–1032**
 - applications 1031
 - fixture labeling 1032
 - limitations 1031
 - selection factors 1031
 - rheostats, eliminate **1091–1092**
- Lighting, efficiency standards.** *See* Efficiency codes, laws & standards
- Lighting, fixture layout**
 - & reflective space surfaces. *See* Lighting, reflective space surfaces
 - accommodate all activities **1139–1141**
 - applications 1139–1140
 - avoid duplication 1140
 - area lighting 1131
 - circuit layout **1141–1143**
 - cost 1142–1143
 - for convenient control **1145–1146**
 - for daylighting 1107, 1142
 - methods 1142–1143
 - relay systems 1143, **1144**
 - with programmable controller **1144**
 - cove lighting 1132
 - downlights 1132, 1135–1136, 1139
 - emergency lighting 1139
 - exterior lighting 1132
 - glare, avoiding 1431
 - glare shields 1431
 - indirect lighting 1136–1138
 - inside ceiling plenum 1138
 - light distribution pattern **1481–1482**
 - diffusers, effect of 1481–1482
 - fixture shape, effect of 1481
 - how to measure 1482
 - IESNA Handbook table 1481
 - improving when replacing diffusers 1153–1154
 - lamps, effect of 1481
 - of lamps 1442–1443
 - maintenance lighting 1140
 - relocate fixtures **1133–1134**
 - remove excess fixtures **1130–1132**
 - appearance 1131
 - applications 1131–1132
 - visual quality 1130–1131
 - substitute more efficient fixtures **1135–1138**
 - task lighting. *See* Task lighting
 - transit lighting 1139, 1142
 - wall washers 1132
- Lighting, fluorescent** 1443, **1459–1469.** *See also* Lighting efficiency improvements, fluorescent & daylighting 976
 - ballasts, electronic
 - & lamp efficiency 1464, 1468
 - dimming with 1468
 - efficiency 1059–1060
 - electrical interference 1062, 1443
 - frequency of lamp current 1061
 - harmonic distortion 1062–1063, 1443
 - how they work 1467–1468
 - lamp connections 1061
 - noise 1062, 1443
 - power factor 1062
 - reliability 1063
 - retrofitting 1060
 - service life 1063

- ballasts, hybrid 1060, 1467
- ballasts, in general **1467–1468**
 - ballast efficiency factor (BEF) 1061
 - ballast factor 1060–1061
 - certification 1063
 - crest factor 1061–1062
 - efficiency 1061
 - energy losses 1440–1443
 - filament operation 1061
 - harmonic distortion 1062–1063
 - lamp compatibility 1060
 - purpose of 1467
 - temperature, starting 1062
 - wattage rating 1060
- ballasts, magnetic
 - capacitor, power factor correction 1467
 - capacitor, starting 1467
 - efficiency 1467
 - how they work 1467
 - lamp connections 1061
 - noise 1062, 1443
 - power factor 1062, 1443, 1467
 - reduced-wattage 1059
 - reliability 1063
 - service life 1063
- color rendering 1441–1443
 - phosphors, effect on 1461
- compact fluorescent units
 - ballast efficiency 1440–1443
 - color, lamp 1441–1443
 - color rendering 1029, 1441–1443
 - decorative options 1443
 - dimensions 1028
 - efficiency 1027, 1437–1443
 - electrical interference 1029, 1443
 - for task lighting 1128
 - harmonic distortion 1029–1030, 1443
 - light distribution pattern 1028, 1442–1443
 - lumen degradation 1437–1443
 - lumen output 1026–1027, 1437–1443
 - noise 1443
 - power factor 1443
 - quality 1027–1028
 - reflector lamps 1034
 - replacing incandescent lamps 1440. *See also* Lighting efficiency improvements, incandescent: lamps, substitute compact fluorescent
 - screw-in extension lamps 1034
 - service life 1027–1028, 1437–1443
- temperature, effect on output 1029, 1442–1443
- temperature, starting 1029, 1442–1443
- time to restart 1442–1443
- time to start 1442–1443
- tube replacement 1029
- dimming **1066–1068**, 1440–1443
 - ballasts for 1061
 - efficiency 1066–1067
 - equipment for 1067–1068
 - how it works 1067
 - lamp compatibility 1067–1068
 - reliability 1068
 - turndown 1066–1067
 - where to consider 1066
- efficiency
 - & cost 1461
 - & use of mercury 1460
 - ballasts, effect on lamp efficiency 1468
 - buffer gas, effect of 1461–1463
 - lamp shape, effect on 1464
 - of ballasts. *See herein* ballasts
 - operating temperature, effect on 1464
 - phosphors, effect on 1461
 - range of values 1437–1443
 - starting method, effect of 1463, 1468
 - temperature, effect on 1464
- environmental problems 1045, **1468–1469**
- for task lighting 1128
- frequency of lamp current 1463–1464, 1464
- how it works **1459–1464**
- lamp components **1459–1464**
 - activators 1461
 - argon 1461
 - buffer gas 1461–1464
 - electrodes 1459–1460, 1463–1464
 - filaments 1061
 - krypton 1463
 - mercury 1459–1460
 - phosphors 1459, 1460–1461, 1463
 - starting gas 1463
- lamps
 - ballast compatibility 1055
 - color, lamp 1055–1056, 1441–1443
 - color rendering 1435, 1441–1443
 - cost 1056
 - efficiency 1055
 - filament operation 1055
 - high-efficiency, characteristics 1054–1056
 - light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen output 1055, 1437–1443
 - mercury in 1460
 - mounting position 1443
 - names for **1465**
 - reduced-wattage, characteristics 1054–1056
 - service life 1056, 1437–1443
 - substitution & mismatch 1440–1443
 - temperature, operating 1056
 - temperature, starting 1056
 - time to restart 1442–1443
 - time to start 1442–1443
 - types of lamps 1464, 1465
 - voltage sensitivity 1056
 - wattage 1055
- light output 1460
- maintenance. *See* Lighting, maintenance
- mercury in 1460
- socket types 1155
- spectrum
 - effect of phosphors 1460–1461
 - of typical lamps 1461
 - ultraviolet 1459–1460
 - visible 1460–1464
- starting aid 1468
- starting methods **1468**
 - instant-start 1463, 1468
 - preheat 1463, 1468
 - rapid-start 1463, 1468
 - starter 1468
 - trigger-start 1468
- temperature, effect on output 1442–1443
- temperature, operating
 - effect on efficiency 1464
 - effect on output 1464
 - temperature, starting 1442–1443
- Lighting, HID 1471–1480.** *See also* Lighting efficiency improvements, HID
- & daylighting 976
- ballasts
 - & capacitors 1076
 - & ignitors 1076
 - ANSI code 1075
 - capacitor, power factor correction 1475
 - constant wattage (CW) 1075, 1474–1475

- constant wattage autotransformer (CWA) 1075, 1474–1475
 - control connections 1076
 - conversion kits 1073
 - crest factor 1075
 - distance from lamp 1076
 - efficiency 1076
 - electrical interference 1443
 - electronic 1076
 - emergency lighting connections 1076
 - energy losses 1440–1443, 1480
 - fixtures per circuit 1075
 - harmonic distortion 1443
 - lamp compatibility 1075
 - lamps per ballast 1075
 - noise 1443
 - power factor 1076, 1443, 1475
 - purpose of 1474
 - reactor 1075, 1076, 1474
 - service life 1076
 - temperature, starting 1076
 - voltage sensitivity 1075
 - capacitors 1076
 - dimming **1079–1080**, 1440–1443
 - applications 1079
 - controls for 1080
 - effect on color 1080
 - effect on mounting position 1080
 - effect on operating temperature 1080
 - efficiency 1080
 - electronic dimming 1079
 - step dimming 1079
 - turndown ratio 1079–1080
 - efficiency, of ballasts. *See herein* ballasts
 - efficiency, of lamps. *See herein* lamps, by type
 - environmental problems 1468–1469
 - fixtures
 - labeling 1077
 - selection factors 1076–1077
 - for task lighting 1128–1129
 - how it works 1471
 - ignitors 1076, 1475
 - lamps, high-pressure sodium **1476–1478**
 - & ignitors 1478
 - color, lamp 1441–1443
 - color rendering 1074, 1441–1443, 1479
 - construction 1471–1474
 - efficiency 1074, 1476–1478, 1479
 - light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen output 1074, 1437–1443
 - mounting position 1074–1075, 1443, 1478
 - service life 1075, 1437–1443
 - spectrum 1471, 1476–1478
 - starting gases 1471, 1478
 - substitute for mercury vapor **1078–1079**
 - substituting for mercury vapor 1478
 - substitution & mismatch 1440–1443
 - temperature, operating 1075
 - time to restart 1442–1443
 - time to start 1442–1443
 - lamps, mercury vapor **1475**
 - color, lamp 1441–1443
 - color rendering 1074, 1441–1443, 1479
 - color rendering index 1475
 - construction 1471–1474
 - efficiency 1074, 1475, 1479
 - hazard, ultraviolet 1474
 - light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen loss 1475
 - lumen output 1074, 1437–1443
 - mounting position 1074–1075, 1443, 1475
 - phosphors 1471, 1475
 - self-ballasted 1025
 - service life 1075, 1437–1443
 - spectrum 1471, 1475
 - starting electrode 1475
 - starting gas 1471, 1475
 - substitution & mismatch 1440–1443
 - temperature, operating 1075
 - time to restart 1442–1443, 1475
 - time to start 1442–1443
 - lamps, metal halide **1475–1476**
 - & ignitors 1476
 - color, lamp 1441–1443
 - color rendering 1074, 1435, 1441–1443, 1479
 - construction 1471–1474
 - efficiency 1074, 1475, 1479
 - hazard, explosion 1476
 - hazard, ultraviolet 1474
 - light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen loss 1476
 - lumen output 1074, 1437–1443
 - metal vapors used 1475–1476
 - mounting position 1074–1075, 1443, 1476
 - phosphors 1471, 1475
 - service life 1075, 1437–1443, 1476
 - spectrum 1471, 1475
 - starting gas 1471, 1476
 - substitute for mercury vapor **1078–1079**
 - substitution & mismatch 1440–1443
 - temperature, operating 1075
 - time to restart 1442–1443, 1476
 - time to start 1442–1443
 - lamps, not requiring ballast 1475
 - photocontrol, limitations with 1105
 - socket types 1155
 - temperature, effect on output 1442–1443
 - temperature, starting 1442–1443
- Lighting, incandescent.** *See also*
- Lighting efficiency improvements, incandescent
 - advantages 1021
 - color, lamp 1451
 - color rendering 1435, 1449–1450
 - compared to sunlight 1449–1450
 - definition 1447–1448
 - dimming **1042–1043**, 1440–1443
 - efficiency limitations 1042
 - electrical interference 1043
 - rheostats, eliminate **1091–1092**
 - types of dimmers 1042–1043, 1091
 - efficiency 1450
 - comparison (table) 1454
 - methods of improving **1451–1453**
 - filament materials 1450–1451
 - filament temperature, effects **1450–1451**
 - service life 1451
 - filament type 1453, 1457
 - & focussing 1453
 - & lamp darkening 1453
 - & light distribution pattern 1453
 - low-voltage 1452–1453, 1453
 - shock resistant 1453
 - vibration resistant 1453
 - how it works **1447–1448, 1448**
 - lamps, all types
 - base types 1457
 - bulb shapes 1457
 - color, lamp 1441–1443, 1451
 - color rendering 1441–1443
 - color-corrected 1024
 - decorative options 1443
 - gases in 1451

- light distribution pattern 1442–1443
 - lumen degradation 1437–1443
 - lumen output 1437–1443
 - mounting position 1443
 - naming of **1457**
 - service life 1437–1443
 - substitution & mismatch 1440–1443
 - tinted 1024
 - lamps, conventional
 - Class B & Class C 1453–1454, 1457
 - krypton filled 1025
 - lamps, reflector
 - ellipsoidal reflector 1034
 - PAR (parabolic) 1033–1034
 - R-series 1033
 - lamps, tungsten halogen 1451–1452
 - cleaning 1152
 - color temperature 1032
 - dimensions 1031
 - efficiency 1032, 1452
 - infrared reflecting coatings 1452
 - krypton in 1025
 - light distribution pattern 1032
 - safety hazards 1452
 - service life 1032, 1452
 - low-voltage 1452–1453
 - lumen degradation **1453–1454**
 - service life 1451, **1453–1454**
 - comparison (table) 1454
 - socket types 1155
 - spectrum **1449**
 - ultraviolet 1451
 - Lighting, low-pressure sodium 1478–1479**
 - ballasts
 - electrical interference 1443
 - energy losses 1440–1443
 - harmonic distortion 1443
 - noise 1443
 - power factor 1443
 - lamps
 - buffer gas 1479
 - color, lamp 1441–1443
 - color rendering 1077, 1441–1443, 1479
 - construction 1479
 - efficiency 1077, 1478–1479, 1479
 - light distribution pattern 1442–1443
 - lumen output 1437–1443
 - operating temperature 1479
 - service life 1075
 - starting gas 1479
 - substitution & mismatch 1440–1443
 - time to restart 1442–1443, 1479
 - time to start 1442–1443, 1479
 - temperature, effect on output 1442–1443
 - temperature, starting 1442–1443
 - Lighting, maintenance**
 - cleaning **1152–1153**
 - & group relamping 1152
 - energy saving 1152
 - halogen lamps 1152
 - how often 1152
 - materials for 1152
 - safety 1152
 - fixture labeling **1155–1157**
 - methods 1156
 - what to say 1156
 - where to do it 1156
 - why to do it 1155
 - fluorescent fixtures 1083
 - group relamping 1437–1443
 - replace darkened diffusers **1153–1154**
 - changing light distribution pattern 1153–1154
 - diffuser materials 1153
 - energy saving 1153
 - where to find replacements 1154
 - task lighting 1121
- Lighting, measurements 1423–1424**
 - brightness 1424
 - candela 1423–1424
 - candle 1423–1424
 - candlepower 1423–1424
 - footcandle 1423
 - footlambert 1424
 - illuminance 1423
 - lumen 1423
 - luminance 1424
 - lux 1423
- Lightweight concrete, as insulation.** *See* Insulation, types: lightweight concrete
- Lithium bromide** 1325
- Load calculations** 1240
- Load shedding**
 - with photovoltaic systems 1272
- Load-commutated inverter** 1355
- Loading dock seals.** *See* Dock seals
- LonMark** 1226
- LonWorks** 1226
- Louvers, for air handling systems.** *See* Air handling systems: envelope penetrations, improve
- Louvers, for shading.** *See* Shading, to reduce cooling load
- Low-emissivity (low-E) coatings**
 - for glazing 937–938
 - for solar control films. *See* Film, solar control
- Low-temperature distribution systems**
 - disadvantages of 432–433
 - with cooling storage 432–433
- Low-voltage lighting.** *See* Lighting, incandescent: low-voltage
- Lumen (definition)** 1423. *See also* Lighting, measurements
- Luminance**
 - definition 1424. *See also* Lighting, measurements
- Lux.** *See also* Lighting, design issues; Lighting, measurements definition 1423
- ## M
- Magnesium, in boiler water** 144, 145–146
 - Makeup air.** *See* Ventilation, outside air
 - heat recovery. *See* Heat recovery, from building exhaust air
 - Makeup water, boiler.** *See* Condensate systems
 - Marking.** *See* Placards
 - MCA ratings (for boilers)** 1295
 - Mercury**
 - characteristics, for lighting 1460
 - environmental hazard 1045, 1468–1469
 - in fluorescent lighting 1045, 1459–1460
 - in HID lighting 1471
 - in low-pressure sodium lamps 1479
 - in mercury vapor lamps 1475
 - in metal halide lamps 1475
 - Metering, electricity.** *See* Electricity pricing
 - Methane**
 - fuel properties of 1247–1249
 - Microwave personnel sensors.** *See* Personnel sensors: microwave
 - Midgely, Thomas** 1332, 1335
 - Mineral wool insulation.** *See* Insulation, types: mineral fiber
 - Montreal Protocol** 1333–1334
 - Motion sensors.** *See* Personnel sensors
 - MotorMaster computer program** 1166

Motors, AC induction

efficiency
 & operating temperature 1172
 & starting current 1172–1173
 & voltage 1172
 comparative characteristics 1163–1164
 estimating, for existing motors 1166–1167
 in new construction 1162
 part-load 1163, 1169
 standards 1167–1169
 test methods 1168–1169
 enclosure types 1173
 energy consumption by 1161
 fractional-horsepower 1163–1164
 frame types 1173
 high-efficiency
 construction features 1164–1165
 cost premium 1166
 savings potential 1165–1166
 how to select 1162–1175. *See also* MotorMaster computer program
 insulation failure, with VFD's 1363–1364
 inverter duty 1363
 multi-speed **1346–1349**
 efficiency characteristics 1348
 number of poles 1347
 prices 1348
 single-phase 1348–1350
 speed ratios 1347
 speeds 1347
 torque characteristics 1348
 types of multi-speed motors 1347
 NEMA Designs 1170, 1171
 operating temperature
 & altitude 1172
 & ambient temperature 1171
 & dirty environments 1172
 & efficiency 1172
 & frequent starts 1171
 & load 1171–1172
 & phase balance 1172, 1173–1174
 & power quality 1172
 & variable-frequency drives 1171–1172
 power factor 1172
 rewinding 1163
 service factor 1169
 single-phase 1163–1164, 1164–1165
 sizing 1169

speed of induction motors
 & number of poles 1170–1171
 & power frequency 1170–1171
 full-load 1170–1171
 slip 1170–1171
 synchronous 1170–1171
 starting current 1172–1173
 temperature ratings 1167, 1171–1172
 of insulation 1171
 torque characteristics 1169–1170
 & full-load speed 1171
 & NEMA Designs 1170, 1171
 & service factor 1169
 breakdown torque 1170
 full-load torque 1170
 locked-rotor torque 1170
 pull-up torque 1170
 starting torque 1170
 variable-frequency drives, for 1174
 voltage 1172
 voltage stress 1361
Motors, direct-current (DC). *See* Drives, direct-current (DC)
Motors, dual drives. *See* Drives, multiple-motor
Motors, high-efficiency, install 1162–1175. *See also* Motors, AC induction
 for air conditioners **756, 766**
 for combustion systems **89**
 for condensate systems **171**
 for cooling compressors **332**
 for cooling system pumps **330**
 for fan-coil units **744**
 for fuel oil pumps **180**
 for heat pumps **766**
 for heat rejection equipment **315**
 for service water systems **496**
 for split systems **766**
 upgrading 1162–1163
 estimating existing motor efficiency 1166–1167
 preparation for 1163
 with variable-frequency drives 1363
Motors, multi-speed. *See* Motors, AC induction: multi-speed
Motors, wound-rotor 1375
 efficiency 1375
 how they work 1375
 slip energy recovery 1375
 speed control 1375
 turndown ratio 1375
 windings 1375

Movable insulation

description 1420
 installation. *See* Insulation, for windows: thermal shutters

Mud room 819

Multi-speed motors. *See* Drives, multi-speed motor; Motors, AC induction: multi-speed

N

National Fenestration Rating Council 943

Natural gas

& fireside cleaning. *See* Boiler plant maintenance: fireside cleaning; Soot blowers
 burners for. *See* Burner systems, fuel
 cleaning of gas-fired furnaces 798
 flue gas heat recovery with. *See* Economizers, boiler
 fuel for high-efficiency boilers 1294
 fuel for high-efficiency furnaces 799
 fuel for high-efficiency water heaters 464–465
 fuel properties of 1247, 1247–1249

Navy showers 450

NEMA motor efficiency ratings 1167–1169

Net output (boiler rating) 1295

Non-fossil energy sources 1267–1282

biomass. *See* Biomass combustion
 geothermal. *See* Geothermal systems
 passive solar heating. *See* Solar heating, passive
 photovoltaic. *See* Photovoltaic systems
 solar cooling. *See* Solar cooling
 solar heating, active. *See* Solar heating, active
 solar thermal power generation. *See* Solar thermal power systems
 waste product combustion. *See* Waste product combustion
 water power. *See* Hydropower, local
 wind energy. *See* Wind energy systems

Notching, in variable-frequency drives 1360, 1361, 1364

O**Oil.** *See* Fuel oil**Open-loop controls** 1381**Optimum-start controls** 1201for air handling systems. *See* Air handling systems, minimize operationfor boiler plant. *See* Boiler plant, minimize operation**Orifice flowmeters** 1235**Orifice, refrigerant metering** 1301**Orifice traps.** *See* Steam traps**Orsat analyzer** 49**Overrides**

for personnel sensors 1211

for time controls 1203–1204

Oxygenin boiler water. *See* Water testing, boiler waterin flue gas. *See* Air-fuel ratio; Boiler efficiency testing**Oxygen test, combustion.** *See* Boiler efficiency testing**Oxygen trim systems.** *See* Air-fuel ratio: automatic controls**Ozone**

& refrigerants 1335–1336

definition 1335

from electrostatic filters 542

ozone layer 1335

P**Passes, in boilers** 1289**Passive infrared motion sensors.** *See* Personnel sensors: infrared**Passive solar heating.** *See* Solar heating, passive**Peak shaving**

with cooling storage 407

Perlite. *See* Insulation, types: perlite**Personnel sensors** 1205–1212

adaptability 1211

audible sound 1206–1207

coverage pattern 1208–1209

daylight override 1210

delay in turning off 1210

electrical characteristics 1211–1212

false activation 1210

for air handling systems 513–514

for heating & cooling units 714

for lighting control 1109–

1110, 1208

for quick-acting vehicle doors 852–853

for urinals 453

how to cover large areas 1211

how to install 1207–1212

how to limit area of control 1210

how to select 1207–1212

infrared 1205–1206

light beam 1206–1207

microwave 1206

mounting location 1209–1210

overrides for 1211

passive infrared 1205–1206

placards for 1212, 1215

range 1208–1209

safety issues 1207–1208

sensitivity 1208–1209

sensitivity to space layout 1211

sound sensing 1206–1207

tread switches 1206

types 1205–1207

ultrasonic 1206

where to use 1205

Petroleum. *See* Fuel oil**Phase balance, electrical power**

& motor failure 1172, 1173–1174

causes of imbalance 1173–1174

Phosphors. *See* Lighting,

fluorescent; Lighting, high

intensity discharge

Photocontrolsfor exterior lighting. *See* Lighting, control of: by photocontrol, for exteriorfor interior lighting. *See* Lighting, control of: by photocontrol, for interior**Photoelectric controls.** *See*Photocontrols. *See also* Light beam switches**Photography, lighting for** 1441**Photons**

in incandescent lighting 1447–1448

in light emission 1447–1448

Photovoltaic systems 1271–1273

applications 1272

connection to public utilities 1273

development status 1272

economics 1273

environmental issues 1273

generating capacity 1272–1273

photovoltaic cells 1272

PURPA, effect of 1273

system types 1272

Pilot light. *See* Burner systems, fuel**Pipe tunnels**

limit ventilation to conserve heat 216–217

pipe insulation in 213

Pitot tubes 1234–1235**Placards** 1213–1217

appearance 1089, 1216

content of 1214

coordination 1089

examples of 1214–1215

for air handling system controls 584, 641, 643

for air handling system time controls 512, 514, 515

for boiler heat collecting hoods 223

for boiler plant scheduling controls 21, 32

for chilled air temperature setting 608

for chiller plant scheduling controls 248

for door openers 832

for door stops 812

for door switches 716

for efficient water use 450

for evaporator isolation valves 258

for fan speed controls 592

for flushing water heaters 471

for heat pump loop systems 790

for heating & cooling units 704–707

for hot water temperature 460

for interruptible water heating 475, 478

for kitchen fan 1214

for light fixtures

1023, 1030, 1032, 1035, 1049,

1050, 1053, 1056, 1063, 1065,

1077, 1078–1079, 1130, 1155–

1157, 1215

for light shelves 1005

for lighting controls 1086–1089, 1094

appearance 1089

for daylighting 1107

for photocontrols 1107

for programmable controllers 1144

for timed-turnoff switches 1112

how to design 1086–1087

materials 1089

where to install 1086, 1087–1089

why needed 1086

for lighting dimmers 1043

for motion sensor controls 1215

for openable windows 1214

for passive solar heating 1011

for personnel sensors 1212

for quick-acting vehicle doors 853

for radiator controls 723

for refrigerant liquid level indicator 343

for refrigerant purge units 351

- for revolving doors **817**
- for roof accesses 869
- for shading devices 933
- for space air vents 871
- for steam trap test valves 205
- for storage water heating 475
- for suspended ceilings 887
- for swing doors 842, 845
- for thermostats
 - 599, 602, **683**, 697, 1214
 - with VAV systems **662–663**, 665, 668
- for time controls 1202
- for timer switch 1214
- for vacuum condensate systems 733
- for variable-flow pumping 329
- for window shades 1008
- for window switches 716
- how to attach 1216
- materials for 1215–1216
- system diagrams 1215
- updating 1216–1217
- where to use 1213
- why needed 1213
- Poise (viscosity unit)** 175
- Polarization, of light** 1433–1434
- Polling, control signal.** *See* Control signal polling
- Polyethylene film, as vapor barrier** 1392
- Polyisocyanurate insulation** 1398
- Polystyrene insulation** 1398
- Polyurethane foam insulation** 1398
- Pontiac fever** 565
- Power factor**
 - electricity charge for 1256
 - explanation of 1256
 - of capacitors 1256
 - of DC motors 1372
 - of electronic ballasts 1062
 - of fluorescent lighting 1443
 - of HID lighting 1076, 1443
 - of incandescent lighting 1256, 1443
 - of magnetic ballasts 1062, 1256
 - of motors 1172, 1256
 - of variable-frequency drives 1361, 1369–1370
 - of variable-frequency motor drives 1256
- Power quality problems.** *See* Wave-form distortion, electrical power
- Power transistors** 1355
- Pre-rotation vanes.** *See* Inlet guide vanes
- Preheat coils.** *See* Air handling systems: freeze protection
- Pressure, building**
 - & building penetrations. *See* Air handling systems: envelope penetrations, improve
 - ability of air handling system to control 522–524, 533, 548
 - improvement of **532–537**
 - effects of 519–521
 - how to measure 525
- Priming, in boilers.** *See* Water treatment, boiler water
- Programmable lighting controls.** *See* Lighting, control of
- Programmable thermostats** 1202
- Propane**
 - fuel properties of 1247
- Propeller flowmeters** 1233–1234
- Proportional-integral-derivative (PID) controls.** *See* Controls, characteristics of: proportional-integral-derivative (PID)
- Public Utilities Regulatory Policies Act (PURPA)**
 - and hydropower 1278
 - and photovoltaic systems 1273
 - and wind power 1276
- Pulse width modulation (PWM) drives.** *See* Drives, variable-frequency
- Pump curves.** *See* Pumps, centrifugal
- Pumping, high-temperature water** 165
- Pumping, hot water recirculation** 492–494
 - how to control 493–494
 - insulation, effect on pump power 493
 - pump energy requirement 492–493
 - purpose 492
- Pumping, service water pressure** 480–483, 484–487, 488–491
 - analysis of system energy use 481
 - exploit utility pressure 482–483
 - for hot water 483
 - improving, with multiple pumps **484–487**
 - adapting to changing water usage 484–485
 - adapting to various pressure needs 485–486
 - minimizing pressure fluctuation 484–485
- pump sequencing 484
 - reserve pumps 484
 - variable-speed pumps, not 486
- improving, with pressurizing tank **488–491**
 - cost 488
 - efficiency 488
 - freeze protection 491
 - how to select capacity 490
 - how to select pumps 490
 - pressure fluctuations 489–490, 490
 - tank, closed pressurizing 490
 - tank, gravity 489–490
 - pressure requirements 482
 - where to improve 480

Pumping traps 165
Pumping, variable-flow, chilled water 319–329

- CHW temperature reset, effect of 325
- control of chiller loading 324, 326–327
- energy saving 321–322
- higher chiller efficiency 321–322
- less pump energy 321
- reduced cooling load 322
- layout, basic 319–321, 322–325
 - bypass line 324
 - distribution pumps, control of 324–325
 - evaporator check valves 323
 - evaporator circulation pumps 323
 - features of 319–321
 - starting & stopping, chillers & pumps 323–324
 - throttling valves on loads 323
- layout, variations 325–329
 - chiller ahead of bypass line 327–328
 - chiller in return line 328
 - diverse load pressures, accommodating 325–326, 326
 - ganged evaporator pumps 325
 - mixed chiller types 325
 - preferential chiller loading 327–328, 328
 - when connecting chiller plants 328–329
 - whether to install 319, 322

Pumps, centrifugal 1339–1345

- affinity laws 1340
- efficiency 1340–1341
 - & impeller compromises 1344
 - & internal leakage 1345
 - & liquid viscosity 1344
 - & mechanical friction 1345
 - & pump size 1344
 - & specific speed 1180, 1344
 - & surface roughness 1345
- how to select for efficiency 1344–1345
- flow rate 1339
- how they work 1339
- how to adjust output 1340
- impeller 1339
 - pump characteristics, effect on 1339–1340
- impeller trimming **1178–1182**, 1340
 - & system improvements 1182
 - analysis of 1178
 - efficiency, effect on 1178–1180
 - for chilled water pumps **318**
 - for service water pumping **495**
 - how to accomplish 1182
 - how to calculate 1181–1182
 - where to consider 1178, 1180
- multi-stage 1339
- names of types 1339
- operating point 1340–1341
- power input 1339
 - formula for 1342
- pressure output 1339
- pump curves 1342
 - flatness of 1342
- specific gravity, effects of 1339–1340
- specific speed 1344
- suction head (NPSH) 165
- system curves 1180, 1343–1344
- throttling output **1183–1185**
 - analysis of 1183
 - for chilled water pumps **319**
 - how to measure saving 1185
 - how to set 1185
 - valves for 1183–1185
 - where to consider 1185

Pumps, steam-powered condensate movers 165**Purge cycle, air handling system 553–554**

- how to control 553–554
- humidity problems 553
- in VAV systems 554
- where to consider 553

Purge units, refrigerant 1301

- for ammonia 350–351
- how they work 348–349
- install efficient units **350–351**
 - advantages of 350
- operate properly **347–350**
 - energy saving 347
 - how to check 349
- refrigerant loss from operation 349
- system damage from neglect 347–348
- with idle chillers 349
- where they are needed 347

PURPA. See Public Utilities Regulatory Policies Act**PWM (pulse width modulation)**

- drives. See Drives, variable-frequency**

Pyrolytic coatings. See also Low-

- emissivity (low-E) coatings
- description 938
- durability 938, 942
- efficiency 938

Pyrometers 1230–1231**Q****Quartz lamps. See Lighting, incandescent: lamps, tungsten halogen****R****R-value. See Thermal conductivity****Radiation, heat. See Heat: radiation****Radiators**

- air flow, ensure adequate **725–727**
- control, of steam units
 - vacuum condensate system. *See Vacuum condensate systems*
 - why difficult 731–732
- control, provide localized **738–739**
- control, to minimize operation. *See Heating & cooling units, minimize operation*
- control valves, manual
 - improve access **724**
 - replace with thermostatic. *See Radiators: control valves, thermostatic*
- control valves, thermostatic
 - accommodate vacancy 722
 - energy saving 721
 - location 722
 - maintenance requirement 723
 - types of thermostatic valves 721–722
- definition 719

electric, eliminate **736–738**

- alternative heating equipment 737–738
- cost saving 736
- fuel availability 736–737
- heat trapping against wall, avoid **727**
- insulate from wall
 - energy saving 729
 - how to do it 730
 - where it matters 729
- knocking, cause of 731
- steam, convert to hydronic **733–735**
 - alternative heating units 734
 - benefits 734
 - energy saving 733–734
 - expansion tank 735
 - pumps 735
 - thermostatic controls 735
 - using existing boilers 734
 - using existing piping 734
 - using existing radiators 734–735
 - with VAV systems 622

Radon

- building pressure, effect on intake 520
- danger of 565
- description 565
- entry through air handling systems 565
- from soil 565
- from water sources 565
- reducing, by increased ventilation 521
- removal, by carbon filter 541
- where it occurs 565

Ratchet charges, electricity 1255**Rate schedules, electricity 1251–1253****Reactor ballasts, for HID lighting 1474****Receiver, refrigerant**

- adding to system 345–346
- description 1301
- in liquid overfeed systems 1317
- liquid level indicator in 343
- purposes of 345

Recirculation, hot water. See also Pumping, hot water recirculation & water temperature 460 infection hazard 459**Recirculation, in heat rejection**

- equipment. See Heat rejection equipment, efficient installation: avoid air recirculation**

Reflectance, reflectivity (of light)

- 1286–1287

Reflectors, fluorescent fixture. *See* Lighting efficiency improvements, fluorescent: reflector retrofits

Refrigerant charge
 effects of improper 342
 how to measure 342–345
 condensate subcooling 345
 evaporator line sight glass 345
 refrigerant level indicators 342–343
 refrigerant pressures 343–345
 suction superheat 345
 maintain proper **342–346**
 how to add refrigerant 346
 whether to add receiver 345–346

Refrigerants 1331–1338
 availability 1334–1335
 azeotropes 1335
 CFC (chlorofluorocarbon) 1333–1338
 charge. *See* Refrigerant charge
 chlorine in 1333–1334
 definition 1299, 1332
 efficiency characteristics 1303, 1305
 energy efficiency 1337
 & global warming 1337
 environmental issues 1331–1338
 explosion potential 1337–1338
 flammability 1337–1338
 global warming potential (GWP) 1336–1338
 halocarbon 1332–1338
 HCFC (hydrochlorofluorocarbon) 1333–1338
 HFC (hydrofluorocarbon) 1333–1338
 how to select 1334–1338
 latent heat 1332
 leakage. *See* Cooling system leakage
 factors causing 1336
 in ozone depletion 1336
 mixtures 1335
 naming system 1332–1333
 ozone depletion potential (ODP) 1335–1336
 phase-out of chlorine-containing 1333–1334
 Clean Air Act schedule 1333
 Montreal Protocol schedule 1333–1334
 pressure, condensing 1338
 pressure, evaporating 1338
 properties of 1331–1332
 purge units for. *See* Purge units, refrigerant

selecting 1300
 specific heat 1332
 substitution of types 1333–1334
 when replacing compressor 334
 superheat 398
 toxicity 1337

Refrigeration. *See* Cooling

Reheat, in air handling systems. *See also* Air handling systems, by type
 economizer cycle, effect on savings 547–548

Relief air. *See also* Exhaust air
 definition 528
 heat recovery. *See* Heat recovery, from building exhaust air

Renewable energy sources. *See* Non-fossil energy sources

Reserve equipment. *See* Standby equipment

Rod cells (vision) 1429, 1434

Roller shades. *See* Shading, to reduce cooling load: by internal fixtures

Roof hatches, install efficient 869–870
 ease of use 869
 how to install 869
 how to select 869
 maintenance 870
 signage for 869

Rotameters 1235–1236

Rotary cup burners. *See* Burner systems, fuel: types: oil, rotary cup

Runaround loop 559. *See also* Heat recovery, from building exhaust air

Rundown timers. *See* Timed-turnoff switches

S

Sample cooler, boiler water 149

Saybolt Seconds 175

Screw compressors. *See* Compressors, cooling, screw

Scroll compressors. *See* Compressors, cooling, scroll

Scroll housing dampers, for fans 1191

Scrubbers, flue gas 1250

Seasonal energy efficiency ratio (SEER). *See* Efficiency ratings, cooling

SEER. *See* Efficiency ratings, cooling

Sensors
 air flow, to control air handling systems 525, 534–536
 enthalpy. *See* Enthalpy
 flue gases
 for boiler efficiency testing. *See* Boiler efficiency testing
 for controlling air-fuel ratio. *See* Air-fuel ratio: automatic controls
 for flow measurement. *See* Flow measurement
 indoor air pollutant, to control ventilation **530**
 motion. *See* Personnel sensors
 outside air
 how to install 247–248

Series-connected evaporators 1320–1321

Service factor (motors) 1169

Service water. *See* Water, service

Setback thermostats. *See* Thermostats: setback

Setpoint. *See* Controls, characteristics of

Sex, safe 51

Shading coefficient
 definition 932
 of internal shading devices 932

Shading, to reduce cooling load
 azimuth, need to determine 927
 by external fixtures **919–929**
 & daylighting 922
 & fire egress 927
 & passive solar heating 923
 & property lines 927
 appearance 923
 attachment 925
 awnings 920–921
 balconies 919
 controls for movable 925
 design issues 921–927
 eaves 919–920
 energy saving 919
 horizontal shelves 919
 longevity 923–925
 louvers 920, 921
 mesh materials 921
 methods 919–921
 orientation 927
 overhangs 919–920
 penetrations of wall 927
 removable 925
 roll-up blinds 921
 sheathing 956
 vertical fins 920
 view, effect on 921
 where to consider 919

by internal fixtures **930–933**
 & daylighting 930, 932
 & fire egress 932
 & heat loss 930
 & passive solar heating 930–932
 appearance 932
 controls for movable 932
 design issues 932
 draperies 931
 energy saving 930, 932
 glare 932
 installation 932
 longevity 932
 louvers 931
 methods 931–932
 orientation 932
 roller shades 931
 venetian blinds 931–932
 vertical blinds 931–932
 view, effect on 932
 where to consider 930
 within glazing units 940

by reducing glazing area **949–951**
 & daylighting 950
 & passive solar heating 950
 appearance 950–951
 energy saving 949
 how to plan 949–951
 security benefit 951
 view 950
 where to consider 949

by solar control film. *See* Film, solar control

by surface finish **954**
 absorption 955–956
 emittance 955–956
 energy saving 955
 how to select 956
 sheathing 956
 where to use 954–955

by trees & foliage **961–964**
 & daylighting 961
 & passive solar heating 961
 appearance 961
 disadvantages 961–962
 energy saving 961
 energy saving, delay 961
 how it works 962–963
 how to preserve 964
 how to select species 963
 maintenance required 962
 subsidies for 964
 usable space, increasing 961
 where to consider 961
 where to plant 963

reflection from adjacent features 928
 shading by adjacent objects 928
 to reduce demand charges 917

Shower heads
 & efficient faucets 446
 flow restrictors, avoid 447
 install efficient **445–448**
 cost 445
 ease of use 446
 how to select 447
 integral valve, avoid 446
 personal preferences 445–446
 spray characteristics 445–446
 water saving 445
 maintenance **441–442**, 447

Showers
 encourage efficient use **450**
 faucets, efficient **448–449**

Sick building syndrome
 & envelope insulation 1397
 & envelope penetrations. *See* Air handling systems: envelope penetrations, improve
 & ventilation 521
 air cleaning to avoid **539–546**
 microorganism growth in cooling coils **544**
 microorganism growth in cooling towers 564–565

Signs. *See* Placards

Silicates, in boiler water
 144, 145, 148

Silicon controlled rectifier (SCR)
 1355

Skylights. *See* Daylighting, by skylights. *See also* Glazing passive heating with. *See* Solar heating, passive

Slip energy recovery, wound-rotor motors 1375

Slip, in AC motors 1347

Sludge
 in boilers 143, 144
 in fuel oil storage 179

Slurry ice storage systems 424–426, 426–427

Smart building controls. *See* Energy management control systems

Smoke production, of insulation materials 1396

Socket adapters
 for fluorescent fixtures 1048, 1070

Soda-lime process 146

Soft start
 in variable-frequency drives 1367

Softening, water. *See* Water treatment, boiler water

Soil
 as heat sink and heat source. *See* Heat pumps: earth-coupled
 as insulation. *See* Insulation, types: soil

Solar collectors 1268
 flat plate 1268
 focussing 1268
 types of collectors 1268
 uninsulated 1263–1264, 1268
 used for heat rejection 1263–1264
 used with heat pumps 787–788, **1263–1264**
 cost advantage 792
 used with heating storage 403

Solar cooling **1269–1271**

Solar heating, active **1268–1271**
 applications 1269–1270
 development status 1270–1271
 economics 1270–1271
 environmental issues 1271
 freeze protection 1269
 heating capacity 1271
 rejection of excess heat 1269
 solar collectors 1268
 stagnation temperature 1269
 sunlight, characteristics **1283–1287**
 system components 1268

Solar heating, passive

& tree shading 961
 by glazed enclosures **1012–1016**
 comfort improvement 1012
 cooling costs, unexpected 1012
 design guidelines 1012–1015
 energy saving 1012
 heating costs, unexpected 1012
 by interior skylight fixtures **1009–1011**
 design guidelines 1010–1011
 energy saving 1010
 by interior window fixtures **1009–1011**
 design guidelines 1010–1011
 energy saving 1010
 comparison with active solar 1415
 design issues **1415–1422**
 appearance 1422
 condensation, limiting 1419–1420
 control, conventional heating & cooling 1421–1422
 control, electric lighting 1421
 control, heat output 1421
 control, solar input 1419

- conventional heating & cooling 1421–1422
 - cost 1422
 - daylighting 1415, 1421
 - distribution of sunlight 1419
 - electric lighting 1421
 - energy saving potential 1417–1419
 - glazing area 1419
 - glazing location 1419
 - heat loss, limiting 1419–1420
 - heat storage, control of 1421
 - heat storage, location 1421
 - heat storage, mass 1420
 - heat storage, materials 1420
 - longevity 1422
 - maintenance 1422
 - snow 1422
 - system components 1415
 - thermal lag 1421
 - water leakage 1422
 - where to use passive solar 1415–1417
 - wind 1422
 - glazing area 950
 - sunlight, characteristics **1283–1287**
 - Solar thermal power systems 1274**
 - and conventional utilities 1274
 - capacity 1274
 - development status 1274
 - economics 1274
 - environmental issues 1274
 - equipment 1274
 - Solstice 1284–1285**
 - Soot blowers 112–114**
 - & fuel type 112–113
 - compressed air blowers 113–114
 - environmental problems 114
 - for firetube boilers 113
 - for watertube boilers 113
 - optimize usage **115**
 - how to schedule 115
 - steam blowers 113–114
 - where to install 112–113
 - with economizers 113
 - Spare equipment.** *See* Standby equipment
 - Specific speed (pumps) 1344**
 - Split systems**
 - definition 1302
 - Split systems (cooling).** *See also* Air conditioners
 - Sputtered coatings 938.** *See also* Low-emissivity (low-E) coatings
 - Stack effect.** *See* Chimney effect
 - Stack gas.** *See* Flue gas
 - Stagnation, in air distribution 620**
 - Stagnation temperature (solar collectors) 1269**
 - Standards.** *See* Efficiency codes, laws & standards
 - Standby equipment, avoid unnecessary operation**
 - by power switching
 - automatic 1195
 - for more than two units 1194–1195
 - for two units 1194
 - rotary switch 1194–1195
 - transfer switch 1194
 - Standby losses, combustion equipment 79**
 - & boiler damage 102
 - explanation 102
 - convection losses 102
 - purging losses 102
 - how to minimize **102**
 - by changing burner type **106**
 - by installing flue damper **104–105.** *See also* Flue dampers, automatic
 - by minimizing burner cycling **106–107**
 - minimizing
 - by installing flue damper **802–803**
 - turbulators, effect of 134–135
 - Standpipe, service water.** *See also* Pumping, service water pressure: improving, with pressurizing tank definition 489
 - Starter (fluorescent lighting) 1468**
 - Starter, motor**
 - soft starting 590
 - Starting aid (fluorescent lighting) 1468**
 - Starting gas**
 - in fluorescent lighting 1463
 - Steam drum (boiler) 1293**
 - Steam pressure.** *See* Boiler steam pressure, minimize
 - Steam traps**
 - capacity range 195
 - construction, operation & leakage tendencies
 - bellows 192–193
 - bimetallic 192
 - disc 193–194
 - float & thermostatic (F&T) 189–190
 - inverted bucket 191
 - orifice 194–195
 - thermodynamic 193–194
 - thermostatic 192–193
 - cost 196
 - don't share 197
 - effects of malfunction 188, 198
 - energy waste from leakage 188, 198
 - failure, causes of 188, 198–199
 - freezing, vulnerability to 196
 - functions of 138, 187–188
 - how to select size 196
 - install most efficient types **187–197**
 - piping details 193, 196
 - pressure differential 195
 - pressure, maximum 195
 - pumping traps. *See* Pumps, steam-powered condensate movers
 - reliability 195
 - repair regularly **198–202**
 - group repair 201–202
 - how often 201–202
 - procedures 202
 - training for 202
 - size 196
 - strainers for 196
 - superheated steam, operation with 196
 - surge capacity 196
 - test regularly **198–202**
 - at start-up 201
 - during warmed-up operation 201
 - hire testing service **207–208**
 - how often 201
 - training for 202
 - testing methods 199–201
 - audible sounds 199–200
 - check condensate vents 199
 - gauge glass on trap 200, 205
 - infrared imaging 201
 - permanently installed devices **203–206**
 - preferred test methods 201
 - proprietary devices 205–206
 - stethoscope 199–200
 - temperature 200
 - test valves 199, **203–205**
 - ultrasonic stethoscope 200
 - types of steam traps 188–195
 - venting, cold system 195
 - venting, warmed-up system 195–196
 - water hammer, vulnerability to 196
- Stefan-Boltzmann Law 1229, 1449**
- Stoke (viscosity unit) 175**
- Storm windows.** *See* Glazing: install supplemental
- Strainer cycle.** *See* Heat rejection equipment, direct cooling by: by strainer cycle

Strainers, cooling water. *See* Water treatment, cooling water

Stratification

in air handling systems. *See* Air handling systems: stratification
in fuel oil storage 179

Strip curtains. *See* Doors, strip curtain

Suction cutoff, reciprocating compressors 1310

Sulfites, for water treatment 146

Sulfur

& acid dew point 1249
& flue gas temperature 1249
as fuel contaminant 1248
heat content of 1247, 1248

Sump heaters, compressor
minimize operation **261, 770**

Sun shading. *See* Shading, to reduce cooling load

Sun trackers, for daylighting. *See* Daylighting, by light pipes

Sunlight, characteristics 1283–1287

atmosphere, effects of 1283, 1285
color rendering 1434–1435
difficulty in using 913
energy content
913, 917, 1283, 1405
glazing materials, effects
1284, 1286
glazing orientation, effects 1285–1286
infrared component 1284
motion of sun 1284–1285
reflection from exterior surfaces
1287
reflection from smooth surfaces
1287
spectrum 1283–1284
ultraviolet component 1284
visible component 1284
wavelengths 1283
weather, effects of 1285

Superheat, refrigerant

how it reduces COP 1318–1319
in expansion valves 1318

Superheat, steam

economizer selection, effect on 120
interferes with measuring condensate to find leaks 214
steam trap issues
bellows traps, do not use with
192, 196
disc traps, chattering 196
inverted bucket traps, running dry
191, 196

orifice traps, leakage through
194–195, 196, 198

to avoid steam line condensation
214

Superheaters, boiler 1290–1291

Surface water, as heat sink and heat source. *See* Heat pumps: surface water source

Surge, in centrifugal compressors
1308

limitation on heat recovery 386

Survey, heat loss. *See* Infrared thermal scanning

Suspended ceilings. *See* Insulation, for suspended ceiling

Swamp coolers. *See* Evaporative space coolers

Switches

for heating & cooling units. *See* Heating & cooling units, minimize operation
for lighting. *See* Lighting, control of
for standby equipment. *See* Standby equipment, avoid unnecessary operation: by power switching
timed-turnoff. *See* Timed-turnoff switches

System curves, pumping

in general 1343–1344

T

Tank, pressurizing, service

water. *See* Pumping, service water pressure: improving, with pressurizing tank

Task lighting 1119–1129. *See also* Lighting, design issues; Lighting, fixture layout

& lighting of adjacent space
1121, 1122

accommodate all activities 1129

adaptability 1121

advantages 1121

aiming 1124–1126

with fixtures 1124–1125

with reflector panels 1126–1127

as fundamental approach 1020

avoid duplication 1129

bounce lighting 1123–1124

& reflector panels 1124

challenges 1119–1121, 1121–1122

controls for 1129

cost 1121, 1122

definition 1119

design effort 1122

efficiency 1121

esthetics 1122

fixture mounting 1126–1128

distance from task 1127

for bounce light 1128

on ceiling 1127

on task 1127–1128

requirements 1126–1127

fixtures 1121

aiming 1124–1125

diffusers for 1123

fluorescent 1083

reflector 1123

surface area 1123–1124, 1428–1429

for office work 1428

glare

from light sources 1119

from reflections of light source
1122–1123

glare shielding 1128

& reflector panels 1128

appearance 1128

geometry of 1128

on fixtures 1128

illumination, uniformity of 1119–1121

lamp types for task lighting
compact fluorescent 1128

efficiency 1128–1129

HID 1128–1129

not incandescent 1128

layout

accommodate all activities 1129

aiming fixtures 1124–1126

bounce lighting 1123–1124

do not duplicate fixtures 1129

fixture mounting 1126–1128

glare shielding 1128

reflector panels 1126

"standard" layout 1119–1121

surrounding area, relationship to
1122

to avoid shadowing at task 1122

maintenance 1121

reflector panels 1126–1127

& glare shielding 1128

shadowing, by the viewer 1121

shadowing, within the task 1122

veiling reflections 1119

visual quality 1121

Temperature

air handling unit discharge

to minimize reheat. *See* Air handling systems, by type

- chilled water
 - maximize, to increase chiller efficiency. *See* Chilled water temperature, maximize
- combustion air
 - air preheater, increase with **126–128**
- condensing
 - chiller heat recovery, effect on. *See* Heat recovery, from cooling equipment
 - lower, to maximize chiller efficiency. *See* Condensing temperature, optimize
- definition of 1229–1230
- flue gas
 - boiler turbulators, effect of. *See* Turbulators, for firetube boilers
 - flue gas heat recovery, effect on. *See* Air preheaters, boiler; Economizers, boiler
 - for boiler efficiency measurement. *See* Boiler efficiency testing
- for rating cooling equipment. *See* Efficiency ratings, cooling: rating temperatures
- of fuel oil
 - adjust, to control viscosity **174–175**
- of combustion air
 - recover boiler room heat **218–223**
- of hot service water. *See* Hot water temperature
- of pipe tunnels
 - maximize, to minimize heat loss **216–217**
- outside air
 - for free cooling, in chilled water systems. *See* Heat rejection equipment, direct cooling by
 - for free cooling, through air handling system. *See* Air handling systems: purge
 - cycle; Economizers, outside air to control air handling system running. *See* Air handling systems, minimize operation: by optimum-start control
 - to control boiler plant running **25–26**
- ratings of motors. *See* Motors, AC
- induction: temperature ratings
- setback. *See* Thermostats: setback
- supply air setting. *See* Air handling systems, by type
- wet-bulb. *See* Wet-bulb temperature
- Tempering valve, hot water** 475
- Terminal units.** *See also* Air handling systems, by type
- Thermal breaks, glazing** 936–937
- Thermal conductivity**
 - of materials. *See* Insulation, types
 - R-value
 - definition 1395
 - of common materials (table) 1395
 - U-value
 - definition 1395
- Thermal shutters.** *See* Movable insulation
- Thermal storage, cooling** **405**
 - applications 406
 - benefits 407–409
 - chiller capacity, reduced 407–408
 - condensing temperature, lower 408
 - distribution equipment, smaller 408
 - electricity cost, reduced 407, 412
 - heat recovery, increased 409, 414
 - reserve cooling capacity 408
 - chiller capacity for 415
 - chiller types for 415
 - control strategy 414
 - deregulation of utilities, effect of 411
 - design issues, general 431–435
 - alarms 416
 - charging storage vs. direct cooling 433
 - controls 416, 433–435
 - distribution system pressure 431–432
 - matching distribution temperatures 432–433
 - disadvantages 409–411
 - economic risk 411
 - energy losses 409–410
 - operational burden 410–411, 411, 412, 416
 - space requirement 410, 416
 - electric vehicles, effect of 411
 - evaporator configuration 415, 417–418
 - how to approach 411–416
 - in heat pump loop systems 781, **794**
 - load profiles 411
 - low-temperature distribution, use with 432–433
 - maintenance 416
- negotiating with electric utility 412–413
 - forgiveness clause 413
 - metering arrangements 413
 - rates 412
- not an energy conservation measure 406, 409–410
- ownership options 412
- peak shaving with 407
- staffing 416
- status of 406–407
- storage capacity, cooling 407, 414–415
- storage capacity, heat recovery 415
- storage equipment 415, 416
- system connections 416
- system layout 416
- systems, eutectic storage media 430–431
 - charge, difficulty of measuring 431
 - development status 430
 - disadvantages 431
 - efficiency 430
 - for pre-cooling 431
 - heat exchanger limitations 431
 - phase change temperature 431
 - storage tank 430–431
 - volume required 430
 - with absorption cooling 431
 - with free cooling 431
- systems, ice capsules 423–424
 - advantages 424
 - capsule freezing problems 424
 - discharge characteristics 424
- systems, ice on coil, coil melt 422–423
 - advantages & disadvantages 422
 - storage unit construction 423
 - system connections 423
- systems, ice on coil, external melt 419–422
 - advantages 419–420
 - alternate use for heat storage 422
 - DX storage units 420
 - efficiency 419–420
 - ice bridging 420
 - irregular melting 420–422
- systems, ice shedder 417–419
 - advantages 417
 - efficiency 418
 - evaporator 417–418
 - heat exchanger 419
 - storage tank 418–419
- systems, ice storage, in general 416–417

- systems, liquid chilled water 427–430
 combination with heat recovery storage 430
 economy of scale 428
 efficiency 427
 how to measure charge 430
 storage using diaphragm in tank 430
 storage using multiple tanks 428–429
 storage using siphon baffles 429
 storage using stratification 429
 storage volume required 427–428
 temperature matching to distribution system 428
 systems, separated slurry 426–427
 advantages & disadvantages 426–427
 evaporator 427
 storage tanks 427
 systems, stored slurry 424–426
 advantages 425–426
 evaporator 425
 heat exchanger 425–426
 storage tank 425
- Thermal storage, heated water 400–404**
 cost saving 400–401
 equipment for 401
 energy saving 400–401
 with solar collectors 403
 for cooling equipment heat recovery **400–404**
 demand charges, effect on 400–401
 for preheating service water 402
 for space heating 402–403
 load profiles 400
 storage capacity, how to estimate 401
 storage capacity vs. condensing temperature 403
 in heat pump loop systems 781, **794**
- Thermionic emission**
 definition 1463
 in fluorescent lamps 1463
- Thermodynamic traps.** *See* Steam traps
- Thermography, infrared.** *See* Infrared thermal scanning
- Thermos bottle** 1387
- Thermostatic control valves.** *See* Valves, control
- Thermostatic traps.** *See* Steam traps
- Thermostats**
 anticipators **804**, 1379
 covers, avoid 663
 deadband **600–602**
 & fan cycling 590
 in VAV systems **664–666**
 types 665
 hesitation **600–602**
 let occupants adjust 582
 manual heat/cool switching **597–599**
 placards 1214
 programmable **1202**
 setback
 for heating & cooling units **711**
 for single-zone air handling units **583–584**
 for VAV systems **667–668**
 in digital control system 583
 individually programmable 583
 overrides 668
 pneumatic central control 583
 types 667–668
 space temperature
 how to install 739
 thermometers with 582
- Three-deck multizone systems** 652–653
- Three-pipe systems.** *See* Fan-coil units: 3-pipe systems, convert
- Thyristor** 1355
- Time controls.** *See* Clock controls
- Timeclocks.** *See* Clock controls
- Timed-turnoff switches**
 for air handling systems. *See* Air handling systems, minimize operation
 for heating & cooling units **714**
 for lighting **1111**
 types 512, 1111
- Toilets**
 install efficient **451–452**
 actual performance 451–452
 how to select 452
 maintenance **441**
 water usage standards 452
- Ton (cooling), definition** 1297
- Total dissolved solids (TDS)**
 control with blowdown 148–149
 definition 148
 in condensate 149
 testing for 148–149
- Total internal reflection** 978
- Totalizers** 1236
- Transfer switch**
 for lighting
 to prevent duplicate lighting 1140
 for standby equipment. *See* Standby equipment, avoid unnecessary operation
- Transformers**
 impedance 1359
- Transmittance (of light)** 1286–1287
- Transpiration** 962–963
- Tread switches.** *See* Personnel sensors: tread switches
- Trees**
 air pollution, effect on 961
 carbon dioxide, effect on 961
 for shading. *See* Shading, to reduce cooling load: by trees & foliage transpiration 962–963
- Triple-duct air handling systems.** *See* Air handling systems, triple-duct
- Trochoid compressors** 1314–1315
- Tropic of Cancer** 1285
- Tropic of Capricorn** 1285
- Truck dock seals.** *See* Dock seals
- Tube sheets, boiler** 1289
- Tungsten**
 as lamp filament 1450–1451, 1451–1452, 1453–1454
- Turbine**
 as refrigerant metering device 1301, 1319–1321
- Turbine flowmeters** **1233–1234**
- Turbulators, for evaporator tubes** **286–287**
 effect on flow rate 287
 energy saving 286
 hazards 287
 where to consider 286
- Turbulators, for firetube boilers** **133–135**
 cost 133
 damage to boiler 135
 draft, effect on 134
 fireside cleaning, interference 135
 how they work 133
 standby losses, effect on 134–135
 where to consider 134

U

U-value. *See* Thermal conductivity

Ultrasonic flowmeters 1234

Ultrasonic sensors. *See* Personnel sensors: ultrasonic

Ultraviolet air filters 542–544

Unit ventilators. *See also* Fan-coil units
definition 741

Unloading, reciprocating compressors 1310

Urea formaldehyde insulation 1397

Urinals

flush valves for 454–455

maintenance 441

improve existing **454–455**

install efficient **453–455**

how to select 453–454

water usage standards 453

waterless 453–454

V

Vacuum condensate systems

advantages 169, 732

how they work 169–170, 732

how to retrofit 732

install, for improved heating control
731–733

energy saving 731

maintenance **169–171**

Valves, control

adjusting actuator 603

adjusting for deadband **603–604**

bypass

convert to throttling 323

eliminate in variable-flow systems
322

pump power requirement 322

equipment lacking 323

manual, for radiators

improve access **724**

throttling

in variable-flow systems

321, 323

Valves, water fixture. *See* Faucets

Vane compressors 1314–1315

Vapor barriers **1391–1394.** *See also*

Insulation, for application

& air leakage 1385

definition 1391

how to install 1392, 1393–1394

materials 1392–1393

purposes 1391–1392

venting 1393–1394

Variable-air-volume. *See* Air handling systems, by type

Variable-area flowmeters **1235–1236**

Variable-flow pumping. *See* Pumping, variable-flow

Variable-pitch fans. *See* Fans: variable-pitch

Variable-pulley drives. *See* Drives, variable-pulley

Variable-speed drives. *See* Drives, variable-speed. *See also* Drives, direct current (DC); Drives, multiple-motor; Drives, variable-frequency; Drives, variable-pulley; Motors, AC induction: multi-speed; Motors, wound-rotor

Variable-voltage input (VVI)

drives. *See* Drives, variable-frequency

VAV (variable air volume). *See* Air handling systems, by type

VAV terminals, fan-powered. *See* Fan-powered VAV terminals

Veiling reflections. *See* Lighting, design issues: veiling reflections

Velocity pressure

definition 1234

in flow measurement 1234

of wind 1383

Venetian blinds. *See*

Daylighting; Shading, to reduce cooling load

Ventilation, of attics **957–960**

energy saving 958

how to control 960

how to guide the air flow 958–959

how to move the air 959–960

where to improve 957–958

Ventilation, of pipe tunnels **216–217**

Ventilation, outside air. *See also* Air handling systems, by type

& building penetrations. *See* Air

handling systems: envelope

penetrations, improve

& building pressurization. *See*

Pressure, building

ability of air handling system to

control 522–524

air flow measurement 534–536

improvement of **532–537**

amount needed 521

control, by sensing contaminants

530–531

cost 531

design difficulty 531

identifying critical pollutants 530

sensor maintenance 531

energy effects 519

exhaust fans, air for 522

how to reduce 522

for cooling

by windows 550

economizer cycle. *See* Economizer, outside air

health issues 521

how to measure 524–525

in dual-duct systems 649

in VAV systems 619–

620, 622, 625

optimize **519–526**

reduce, by air cleaning **539–546**

energy saving 539–540

fan pressure requirement 545

hazards 545

in VAV systems 621

methods 540–544

where to install equipment 544–545

with adsorbents 541

with chemical filters 541–542

with electrostatic filters 542

with HEPA filters 540–541

with ultraviolet filters 542–544

reduce, by improving HVAC

equipment 545

reduce, by installing hoods 545–546

reduce, by reducing interior emissions 545

reduce during unoccupied periods

527–529

standards for 521

Venturi flowmeters **1235**

Vermiculite 1388. *See* Insulation, types: vermiculite

Vestibules **820–822**

& door operators 812–813

heating of 821–822

layout 821

quick-acting doors for 840

where to consider 820–821

VFD. *See* Drives, variable-frequency

Vision, human. *See also* Daylighting, design issues; Lighting, design issues

adaptation to brightness 1410, 1429

color 1434. *See also* Lighting,

design issues: color rendering

defects 1435

loss, in dim light 1435

color vision defects 1435

Voltage stress, in motors 1361

Volute, pump 1339

von Karman vortices 1234

Vortex shedding flowmeters **1234**

VVI (variable voltage input)

drives. *See* Drives, variable-frequency

W**Wall washers (lighting)**

eliminate unnecessary 1132
replace with direct lighting 1136–1138
replace with reflective surfaces 1116

Wash basins

confused with urinals 444
efficient fixtures, install **443–445**
for private use 443
for public use 443–444
stoppers, maintenance **441**

Waste heat

as heat source for heat pumps 787, **1264**

Waste product combustion 1280

applications 1280
availability of material 1280
economics 1280
energy content 1280
environmental issues 1280
equipment 1280
types of combustible waste 1280

Water, domestic. *See* Water, service

Water heaters

anode rods 467
booster heaters **462**
direct-contact
construction 464
economics 464
efficiency 464
flue 465
water condition 464–466
efficiency characteristics 463–465
efficiency ratings 466
electric
efficiency 463–465
energy source, select lowest-cost 462
fast-recovery 466
flue dampers. *See* Flue dampers, automatic: for water heaters
flues 465, 467
flush scale **471–472**
for interruptible heating 475
for storage heating 475
fuel-fired
efficiency 463–464
maintenance **470**

infection hazards 459
install efficient **463–467**
install with lowest-cost energy source **463–467**
insulation 465–466
maintenance access 466–467
power venting 467
recovery rate 460
separate, for high-temperature uses **462**
steam-powered
efficiency 463
tank, non-metallic 467

Water heating

control to reduce demand charges **477–478**
interruptible **473**
capacity vs. temperature 475
disadvantages 473
electricity rate benefit 473
how often interrupted 473
how to exploit 473–475
informing occupants 475
safety 475
utility motivation for 476
water heaters for 475
recirculation. *See* Pumping, service water recirculation
solar 1270
storage **473**

Water power. *See* Hydropower, local

Water, service

fixtures. *See* Fixtures, service water
pressurization. *See* Pumping, service water pressure
recirculation. *See* Pumping, hot water recirculation; Recirculation, hot water
temperature setting. *See* Hot water temperature
water heating. *See* Water heaters; Water heating

Water testing, boiler water 148–149

for alkalinity 148
for hardness 148
for iron 148
for oxygen 148
for pH 148
for silica 148
for total dissolved solids (TDS) 148–149, 155
sample cooler 149
who should accomplish 151

Water treatment, boiler water 142–149

& blowdown. *See* Blowdown, boiler & cooling tower water treatment 149
& hydronic system water treatment 149
benefits 142–143
consultant for **150–151**
functions of 150
how to select 150
contractor for **150–151**
functions of 150
how to select 150
effects of neglect 144–145
carryover 145
corrosion, acid 145
corrosion, alkali 145
corrosion, oxygen 144
damage to sealing materials 145
foaming 145
priming 145
reduced heat transfer 144
scale 144
sludge obstruction 144
tube damage 144
tube fouling 117
equipment for **152–153**
chemical feeders 152–153
how to control 152
maintenance 152–153
for hot water boilers 141
hazards 145
methods of water treatment 141, 145–148
to limit carryover
corn starch 148
to limit condensate system corrosion
amines 148–149
dealkalizing 148–149
neutralization 148–149
to prevent acid corrosion
chromates 148
neutralization 148
nitrites 148
to prevent oxygen corrosion
deaerating tank 146
hydrazine 146
sodium sulfite 146
to prevent scaling
chelants 146–148
dispersants 146–148
ion exchange 145–146

- phosphates 146
 - precipitation 146
 - soda-lime process 146
 - softening 145–146
 - zeolite 145–146
 - to remove dirt
 - alum 145
 - cleaning system before filling 145
 - coagulants 145
 - filtration of makeup water 145
 - what determines need for 143–144
 - when shutting down boiler 118
 - who should accomplish 151
 - Water treatment, condensate.** *See* Water treatment, boiler water
 - Water treatment, cooling tower 280–281, 282, 283–284, 285–286**
 - & boiler water treatment 281
 - by bleed 280, **283–284**
 - automatic control for **285–286**
 - cost of 283
 - how to calculate bleed rate 283
 - by chemicals 280
 - automatic equipment for **282**
 - by strainers 280
 - causes of fouling 280–281
 - consultant for **282**
 - contractor for **282**
 - testing makeup water 284
 - Waterside economizer.** *See* Heat rejection equipment, direct cooling by: by waterside economizer
 - Watertube boilers.** *See* Boilers: watertube
 - Waveform distortion, electrical power**
 - & motor overheating 1172
 - by fluorescent ballasts 1062–1063, 1443
 - by HID ballasts 1443
 - by variable-frequency drives 1360–1361
 - introduction to 1357–1360
 - Weatherstripping**
 - for large exterior doors **827–829**, 834–835
 - for personnel doors **809–810**
 - how to install 809–810
 - for storm doors 819
 - for windows **861**, 940
 - Well water.** *See* Ground water
 - Wet-bulb temperature**
 - for control of heat rejection equipment. *See* Condensing temperature, optimize
 - how to measure 270–271
 - Wheeling (electricity rates) 1257**
 - Wien's Displacement Law** 1229, 1449
 - Wind**
 - & building air leakage 1383
 - effect on air handling systems 565
 - Wind energy systems 1274–1276**
 - applications 1274–1275
 - Betz Coefficient 1275
 - capacity of machines 1275
 - connection to public utilities 1276
 - development status 1275
 - economics 1276
 - energy availability 1275–1276
 - environmental issues 1276
 - equipment 1274–1275
 - from tethered blimps 1276
 - ground friction limitations 1276
 - PURPA, effect of 1276
 - topographical requirements 1276
 - wind speeds required 1275–1276
 - Window treatment.** *See* Shading, to reduce cooling load
 - Windows.** *See also* Glazing
 - for cooling ventilation 550
 - inset, for shading 920
 - maintenance **860**
 - openable
 - types of openable windows 940
 - weatherstripping 940
 - passive heating with. *See* Solar heating, passive
 - storm. *See* Glazing: install supplemental
 - Wood**
 - combustion of. *See* Biomass combustion
 - fuel properties of 1247, 1281
 - Wound-rotor motors.** *See* Motors, wound-rotor
- Z**
- Zeolite** 145–146
 - Zone changeover controls** 749–750

